

INDEX

RUBBER CHEMISTRY AND TECHNOLOGY

VOLUME 46, 1973

AUTHOR INDEX

- ABABI, V., see CHAUSHESKU, E., (2) 581
- ABBOTT, T. P., W. M. DOANE, AND C. R. RUSSELL, Starch xanthide-encased powdered rubber— injection molding and extrusion (Abstract), (2) 590
- ALAKI, Y., T. YOSHIMOTO, M. IMANARI, AND M. TAKEUCHI, Study of configurational sequence structures of poly(butadiene)s by carbon-13 proton decoupled Fourier transform nuclear magnetic resonance spectroscopy, (2) 350
- ALARI, G. AND M. BRUZZONE, Europrene (IP) 80 in tread compounds— comparison with natural and other poly(isoprene)s (Abstract), (2) 579
- ALBRECHT, K. -D., Influence of curing agents on rubber-to-textile and rubber-to-steel cord adhesion, (4) 981
- ALEXEEVA, I. K., see BUIKO, G. N., (2) 573
- ALLIGER, G., Review of the overall progress in the field of powder and liquid elastomers— their potential and future (Abstract), (2) 589
- ALTENAU, A. G., see HILTON, A. S., (4) 1035; TURNER, R. R., (5) 1327
- AMBLER, M. R. AND R. D. MATE, Comparison of number average molecular weights calculated by GPC and membrane osmometry, (1) 115
- ANACHKOV, P., see RAKOWSKY, K., (2) 570
- ANFIMOV, B. N., see DONTSOV, A. A., (5) 1285
- ARENSON, N. M., see BUIKO, G. N., (2) 573
- ARNETT, R. L., see STACY, C. J., (2) 470
- ARNOLD, R. G., A. L. BARNEY, AND D. C. THOMPSON, Fluoroelastomers (Review), (3) 619
- ANGERT, L. G., see ZOLOTAREVSKAYA, L. K., (2) 517
- BACSFALVI, V., D. MCINTYRE, AND H. L. STEPHENS, Low angle x ray studies of carbon blacks in poly(butadiene) (Abstract), (2) 588
- BAGLEY, E. J. AND R. J. DENNENBERG, Curing characteristics of starch xanthide-filled elastomers (Abstract), (2) 592
- BARNEY, A. L., see ARNOLD, R. G., (3) 619
- HARTENEV, G. M., see KONGAROV, G. S., (5) 1188
- BEREJKA, A. J. AND N. E. STRUCKER, Butyl L M as a component in elastomeric materials (Abstract), (2) 590
- BERTRAM, H. H., see JAHN, H. -J., (1) 305
- BETZ, G. E., see KOPMAN, L. S., (2) 557
- BIDDISON, P. H., see MARTIN, F. R., (2) 586
- BITTMAN, J., see CHAUSHESKU, E., (2) 581
- BLACKSHAW, G. C. AND K. J. ROBINSON, The cure versatility of Bromobutyl rubber (Abstract), (5) 1334
- BLANCHARD, R. R., Compounding chlorinated poly(ethylene) elastomers for high temperature service (Abstract), (5) 1336
- BORSSELLINO, J. V., E. V. O'GRADY, D. J. SMITH, AND E. H. SORG, A new concept for sealing automotive stationary glass (Abstract), (5) 1333
- BOUSTANY, K., see MORITA, E., (1) 67
- BOUTON, T. C. AND SHINGO FUTAMURA, Solution SBR—a study in copolymerization dynamics (Abstract), (5) 1322
- , see D'AMICO, J. J., (5) 1299
- BOWERMAN, H. H., see NAKAJIMA, N., (2) 417
- BRAGOLE, R. A., Factors affecting the adhesion of paints to non-polar plastics and elastomers (Abstract), (5) 1333
- BRISTOW, G. M., J. I. CUNEEN, AND L. MULLINS, Comparative properties and performance of natural rubber and synthetic poly(isoprene) (Abstract), (2) 555
- BRUZZONE, M., see ALARI, G., (2) 579
- BUIKO, G. N., N. M. ARENSON, I. K. ALEXEEVA, AND A. D. POJARKOVA, Ways of modifying isoprene based tire rubber compounds (Abstract), (2) 573
- BYRNE, P. S. AND H. F. SCHWARZ, Advantages of powder technology in rubber fabricating industry (Abstract), (2) 591

- CAMPBELL, G. A., High resilience cold cure foam—a pilot plant investigation (Abstract), (5) 1329
- CARBONARO, A., V. ZAMBONI, G. NOVAJRA, AND G. DALL'ASTA, Synthesis and elastomeric properties of copolymers of butadiene and 1, 3-pentadiene, (5) 1274
- CARDINA, J. A., The determination of rubber in atmospheric dusts, (1) 232
- CARLSON, D. W., see TURNER, R. R., (5) 1327
- CERNYAK, N. B., see POLYAK, M. A., (2) 566
- CHANDLER, L. A., see JORGENSEN, A. H., (4) 1087
- CHAUSHESKU, E., J. BITTMAN, V. FIEROJU, F. LEBEDE, M. LABE, V. ABALI, K. DREGUSH, AND E. MICHAILESKU, Some aspects concerning structure, properties and use of natural and synthetic cis poly(isoprene) (Abstract), (2) 581
- CHEN, H. Y., see HIRST, R. C., (1) 22
- CHERNAYA, V. V., V. V. DUBROVSKAYA, O. K. KORNILOVA, AND M. I. SHEPELEV, Effect of vulcanization network type on the properties of films prepared from cis poly(isoprene) dispersions (Abstract), (2) 566
- CHIN, S. H., see SCHAEFER, J., (5) 1127
- CHIRICO, V. E., see ULMER, J. D., (4) 897
- CLAXTON, W. E., AND H. C. HOLDEN, An analog heat-flow and cure controller-simulator for rubber, (4) 1103
- COLE, J. O., see PATEL, S. M., (5) 1325
- COLEMAN, M. M., J. R. SHELTON, AND J. L. KOENIG, Raman and ESR spectroscopic studies of accelerator systems. I. Raman spectra of thiuram sulfides and related compounds, (4) 938
- , —, and —, Thermal degradation of vulcanizing systems and its significance to vulcanization mechanisms, (4) 957
- COLLINS, A. M., The discovery of polychloroprene, (2) G48
- COLLINS, E. A., see NAKAJIMA, N., (2) 417
- , see JORGENSEN, A. H., (4) 1087
- COUCH, H. J., see CAMPBELL, G. A., (5) 1329
- COZEWITH, C., see VER STRATE, G., (5) 1322
- CROFT-WHITE, P. G., see HOWD, G. T., (2) 583
- CUNNEEN, J. I., see BRISTOW, G. M., (2) 555
- CURRO, J. G. AND E. A. SALAZAR, Mechanical behavior of O-rings, (2) 530
- DALL'ASTA, G., see CARBONARO, A., (5) 1274
- D'AMICO, J. J., E. MORITA, A. B. SULLIVAN, K. BOUSTANY, K. T. POTTS, J. KANE, AND D. McKEOUGH, The behavior of 2-cyclohexyldithiobenzothiazole and related unsymmetrical disulfides in rubber vulcanization and their mass spectral patterns, (5) 1299
- , see Morita, E., (1) 67
- DANCHENKO, L. A., see FEDYUKIN, D. L., (2) 511
- DAVIES, J. R. AND E. R. RODGER, Improving processing and performance of high and low cis poly(isoprene)s (Abstract), (2) 574
- DAVISON, S. AND G. L. TAYLOR, Sequence length and crystallinity in alpha olefins, (1) 30
- DELLOLLIS, N. J., The use of radio-frequency activated gas treatment to improve bondability, (2) 549
- DE PALMA, E. P., see WOLF, G. M., (5) 1325
- DEMIRAY, H., see LEVINSON, M., (1) 294
- DENNENBERG, R. J., see BAGLEY, E. J., (2) 592
- DERRINGER, D. C., A predictive model for viscosity of filled and plasticized elastomer compounds (Abstract), (5) 1321
- DEVINEY, M. L., see PATEL, A. C., (4) 787
- DEVRIES, K. L., N. B. MOORE, AND M. L. WILLIAMS, Bond rupture during ozone cracking of torsional loaded styrene-butadiene rubber, (2) 540
- DIAMOND, J. E., Comparison and usage of synthetic poly(isoprene)s in tires (Abstract), (2) 577
- DOANE, W. M., see ABBOTT, T. P., (2) 590
- DOGADKIN, B. A., see DONTSOV, A. A., (5) 1285
- DONTSOV, A. A., B. N. ANFIMOV, AND B. A. DOGADKIN, Heterogeneity vulcanization networks in rubbers, (5) 1285
- DREGUSH, K., see CHAUSHESKU, E., (2) 581
- DUBROVSKAYA, V. V., see CHERNAYA, V. V., (2) 566
- DUCHÁČEK, V., Pre-vulcanization inhibitor of sulfur-free thiuram vulcanization, (2) 504
- DUCK, E. W., Economic and technical prospects for synthetic isoprene rubbers (Abstract), (2) 582

- ELKINA, I. A., see TROFIMOVICH, D. P., (2) 580
ERBEN, G., see KLEEMANN, W., (2) 578
ERMILOVA, N. V., see FEDYUKIN, D. L., (2) 511
- FALK, J. C., R. J. SCHLOTT, D. F. HOEG, AND J. F. PENDLETON, New thermoplastic elastomers. Styrene grafts on lithiated polydienes and their hydrogenated counterparts, (4) 1044
FEDEROVA, T. V., see LYKIN, A. S., (2) 575
FEDYAKIN, D. L., T. I. VINOGRADOVA, L. A. DANCHENKO, AND N. V. ERMILOVA, Effect of degree of dispersion of the curing system on the properties of rubber compounds and their vulcanizates, (2) 511
FETTERMAN, M. Q., Filler effect on the heat stability of vulcanized elastomeric compositions, (4) 927
FIEDLER, A. AND A. STAVAROVA, Experience in application of isoprene rubber SKI-3 in Czechoslovakian rubber industry (Abstract), (2) 579
FIELDING-RUSSELL, G. S., see LIVINGSTON, D. I., (4) 1077
FIEROJU, V., see CHAUSHESKU, E., (2) 581
FOLT, V. L. AND R. W. SMITH, Rheology of elastomer blends, (5) 1193
—, see HARMON, D. J., (2) 449
FLORY, P. J. AND H. SHIH, Thermodynamics of solutions of poly(dimethylsiloxane) in benzene, cyclohexane, and chlorobenzene, (2) 338
—, see SHIH, H., (2) 331
FURUKAWA, J., Temperature dependence of ultimate strength and elongation of vulcanized rubber, (1) 242
FUTAMURA, S., see BOUTON, T. C., (5) 1322
- GAJEWSKI, M., Comparison of dynamic properties of synthetic and natural poly(isoprene)s (Abstract), (2) 561
GALATA, L. A., see KOFMAN, L. S., (2) 557
GALYL-OGLY, F. A., Methods of preparation of SKI-3 based vulcanizates approaching natural rubber based vulcanizates (Abstract), (2) 571
GARDNER, I. J. AND G. VER STRATE, Determination of ethyldenenorbornene in EPDM terpolymers, (4) 1019
GARMANOV, I. V., Progress of scientific investigations in the U. S. S. R. that resulted in the industrial production of cis poly(isoprene) (Abstract), (2) 555
GATZA, P. E. AND R. C. McMILLAN, The use of experimental design and computerized data analysis in elastomer development studies (Abstract), (2) 587
GELLING, I. R., The thermal decompositions of amine complexes of zinc bis(dimethyldithiocarbamate), (2) 524
GENCHEVA, P., see RAKOWSKY, K., (2) 570
COBRAN, R. H., see HOFFMAN, R. F., (1) 139
GRAY, D. G. AND J. E. GUILLET, The application of molecular probe technique to a study of polymer crystallization rates, (1) 14
GRECHANOVSKII, V. A., L. S. IVANOVA, AND I. YA. PODDUBNYI, Nature of the cohesive strength of poly(isoprene) SKI-3 and carbon black compounds based on it, (5) 1234
—, see PODDUBNYI, I. YA., (2) 556
GREGG, E. C., JR. AND J. H. MACEY, The relationship of properties of synthetic poly(isoprene) and natural rubber in the factory. The effect of non-rubber constituents of natural rubber, (1) 47
GRINBERG, A. E., see ZOLOTAREVSKAYA, L. K., (2) 517
GOLDSTEIN, C., see MUKHERJEE, D. P., (5) 1264
GUILLET, J. E. AND A. N. STEIN, Study of crystallinity in polymers by the use of molecular probes, (1) 7
—, see GRAY, D. G., (1) 14
—, see LAVOIE, A., (1) 1
GUSTOVA, L. P., see TROFIMOVICH, D. P., (2) 580
- HALLENBECK, V. L., Scorch control of carboxylic elastomers, (1) 78
HARMON, D. J. AND V. L. FOLT, Multidetectors for analysis of the composition of copolymers as a function of molecular size distribution by steric exclusion chromatography, (2) 449
HARPELL, G. A. AND D. H. WALROD, Organic peroxides for cure of ethylene-propylene rubbers, (4) 1007
HARRINGTON, C. J., Profile of the medalist, (2) G45
HASA, J., see ILAVSKÝ, M., (1) 127
HAVLÍČEK, I., see ILAVSKÝ, M., (1) 127

- HAWS, J. R. AND T. C. MIDDLEBROOK, Compounding radial block polymers (Abstract), (2) 588
- HESSE, W. M., G. C. McDONALD, AND E. URBAN, Specific shape characterization of carbon black primary units, (1) 204
- HILTON, A. S. AND A. G. ALTENAU, Mass spectrometric identification of 2-mercaptobenzo-thiozole sulfenamide accelerators in rubber vulcanizates, (4) 1035
- HIROOKA, M., K. MASHITA, S. IMAI, AND T. KATO, Alternating copolymers by complexed copolymerization, (4) 1068
- HIRST, R. C. AND H. Y. CHEN, NMR study of the crystallization kinetics of cis poly (isoprene) (1) 22
- HIVELY, R. A., see PATEL, S. M., (5) 1325
- HOEG, D. F., see FALK, J. C., (4) 1044
- HOFFMAN, R. F. AND R. H. GORRAN, Liquid carboxyl terminated poly(butadiene), (1) 139
- HOGAN, J. M., C. J. PEARSON, T. H. ROGERS, AND J. R. WHITE, Humidity characteristics of HR and hot urethane foams (Abstract), (5) 1328
- HOLDEN, H. C., see CLAXTON, W. E., (4) 1103
- HOWD, G. T. AND P. G. CROFT-WHITE, Isoprenic rubbers in the middle-term future (Abstract), (2) 583
- HUMPIDGE, R. T., D. MATTHEWS, S. H. MORRELL, AND J. R. PYNE, Processing and properties of liquid rubbers, (1) 148
- ILAVSKÝ, M., J. HASA, AND I. HAVLÍČEK, Effect of reference chain dimensions in the molecular theory of viscoelastic behavior of polymer networks, (1) 127
- IMAI, S., see HIROOKA, M., (4) 1068
- IMANARI, M., see ALAKI, Y., (2) 350
- IVANOVA, L. S., see PODDUBNYI, I. Ya., (2) 556
- , see GRECHANOVSKII, V. A., (5) 1256
- IYENGAR, Y. AND D. F. RYDER, Rubber stocks for improved performance of polyester cord tires, (2) 442
- JAHN, H. -J. AND H. H. BERTRAM, The compression set behavior of nitrile rubber, (1) 305
- JANAKIEW, V., see RAKOWSKY, K., (2) 570
- JANSSON, J. F., see STENBERG, B., (5) 1316
- JOHNSON, A. H., AND C. M. LINDEMAN, Elastomeric gasket composition for elevated temperatures (Abstract), (5) 1333
- JORGENSEN, A. H., L. A. CHANDLER, AND E. A. COLLINS, Multiple glass transitions in butadiene-acrylonitrile copolymers. II. Formation of incompatible phases during copolymerization, (4) 1087
- KACHKINA, L. Y., see KOFMAN, L. S., (2) 557
- KANE, J., see D'AMICO, J. J., (5) 1299
- KARMIN, B. K., Structure and properties of synthetic isoprene rubbers obtained with the use of various catalytic systems (Abstract), (2) 555
- , see TITOV, V. V., (2) 560
- KATO, T., see HIROOKA, M., (4) 1068
- KAVCHOK, R. W., see MEYER, G. E., (1) 106
- KAVUN, S. M., see LYKIN, A. S., (2) 575
- KLEEMANN, W. AND G. ERBEN, Experience in application of different types of 1, 4-cis-poly (isoprene) in tire rubber compounds (Abstract), (2) 578
- KLINE, R. H. AND J. P. MILLER, Preparation and activity of polymerizable antioxidants for emulsion rubbers, (1) 96
- KOENIG, J. L., see COLEMAN, M. M., (4) 938, 957
- KOFMAN, L. S., L. A. GALATA, V. G. ZHAKOVA, T. N. MATVEEVA, G. E. BETZ, AND L. Y. KACHKINA, On manufacturing unmodified poly(isoprene) based rubber compounds with high green strength (Abstract), (2) 557
- KOMURO, K., see NOMURA, A., (2) 558
- KONCOS, R., Present and future applications of liquid hydroxyl-terminated poly(butadiene)s (Abstract), (2) 590
- KONGAROV, G. S. AND G. M. BARTENEV, Effect of the compatibility of rubbers on the viscous flow properties of their binary mixtures, (5) 1188
- KORNILOVA, O. K., see CHERNAYA, V. V., (2) 566
- KOSTRYKINA, G. I., see POLYAK, M. A., (2) 566
- KRESGE, E. N., see VER STRATE, G., (5) 1322
- KRISHEN, A., AND R. G. TUCKER, Quantitative determination of the polymeric constituents in compounded cured stocks by Curie point pyrolysis-gas chromatography (Abstract), (5) 1326

- KRUSE, JULIUS, Rubber microscopy (Review), (3) 653
- KUSANO, T. AND K. MURAKAMI, Characterisation of polymers under large deformation. I. Repeated chemical stress relaxation of vulcanized rubbers, (2) 388
- KUZMA, L. J., see SALTMAN, W. M., (4) 1055
- LABE, M., see CHAUSHESKU, E., (2) 581
- LAMOND, T. G., see SIRCAR, A. K., (1) 178
- LAVOIE, A. AND J. E. GUILLET, Estimation of glass transition temperatures from gas chromatographic studies, (1) 1
- LEBEDE, F., see CHAUSHESKU, E., (2) 581
- LEE, T. C. P. AND S. H. MORRELL, Network changes in nitrile rubbers at elevated temperatures, (2) 483
- LEE, W. R., see MYERS, M. E., JR., (2) 464
- LENGYEL, V. AND I. MUZHAY, Replacement of NR by synthetic poly(isoprene)s (Abstract), (2) 581
- LEVINSON, M., H. DEMIRAY, AND S. C. SHEUNG, Pure flexure of a layered orthotropic shell-elasticity study of a tire related problem, (1) 294
- LINDEMAN, C. M., see JOHNSON, A. H., (5) 1333
- LIPKIN, A. M., see ZOLOTAREVSKAYA, L. K., (2) 517
- LIVINGSTON, D. I. AND G. S. FIELDING-RUSSELL, Measurement of creep, (4) 1077
- LYKIN, A. S., S. M. KAVUN, T. V. FEDEROVA, AND N. M. MALEV, The effect of p-nitrosodiphenylamine on green strength and stability of SKI-3 based coating compounds (Abstract), (2) 575
- MACEY, J. H., see GREGG, E. C., JR., (1) 47
- MALEV, N. M., see LYKIN, A. S., (2) 575
- MALOTKY, L. O., see Santee, E. R., JR., (5) 1156
- MAREI, A. I., G. E. NOVIKOVA, G. P. PETROVA, AND G. T. TKACHENKO, Effect of molecular structure on crystallization in SKI-3 rubber and its raw compounds (Abstract), (2) 559
- MARK, J. E., Thermoelastic properties of rubberlike networks and their thermodynamic and molecular interpretation (Review), (3) 593
- MARTIN, F. R. AND P. H. BIDDISON, The effect of tread polymer, road surface, and driving conditions on wear surface characteristics of tires (Abstract), (2) 586
- MARTIN, J. W., 1, 2-Poly(butadiene) resin coagents for peroxide cure of rubber compounds, (1) 275
- MASHITA, K., see HIROOKA, M., (4) 1068
- MATE, R. D., see AMBLER, M. R., (1) 115
- MATTHEWS, D., see HUMPHIDGE, R. T., (1) 148
- MATVEEVA, T. N., see KOFMAN, L. S., (2) 557
- MCDONALD, G. C., see HESS, W. M., (1) 204
- MCINTYRE, D., see BACSALVI, V., (2) 588
- MCKEOUGH, D., see D'AMICO, J. J., (5) 1299
- McMILLAN, R. C., see GATZA, P. E., (2) 587
- MEDALIA, A. I., Elastic modulus of vulcanizates related to carbon black structure, (4) 877
- MEDEL, A. L., Experience in using synthetic 92 per cent cis-1, 4-poly(isoprene) (Abstract), (2) 578
- MEYER, D. A., see SOMMER, J. G., (5) 1330
- MEYER, G. E., R. W. KAVCHOK, AND F. J. NAPLES, Emulsion rubbers copolymerized with monomeric antioxidants, (1) 106
- MEYERS, M. E., JR., A. W. WIMS, AND W. R. LEE, Latex maturation studies by low angle light scattering photometry, (2) 464
- MICHAILESKU, E., see CHAUSHESKU, E., (2) 581
- MIDDLEBROOK, T. C., see HAWS, J. R., (2) 588
- MILLER, J. P., see KLINE, R. H., (1) 96
- MOGHE, S. R. AND H. F. NEFF, Dependence of compression modulus on Poisson's ratio, (1) 286
- MOORE, N. B. see DEVRIES, K. L., (2) 540
- MORITA, E., K. BOUSTANY, J. J. D'AMICO, AND A. B. SULLIVAN, Rubber chemicals from cyclic amines. VII. Cycloalkylthioamines as accelerators and prevulcanization inhibitors, (1) 67
- , see D'AMICO, J. J., (5) 1299
- MORRELL, S. H., see HUMPHIDGE, R. T., (1) 148
- , see LEE, T. C. P., (2) 483
- MORRISSEY, R. T., C. E. WILKES, AND M. J. P. PEKLO, Changing the rate of crystallization of trans-1,4-poly(isoprene) by sulfur crosslinks (Abstract), (5) 1331
- MORSEK, R. J., see WOODS, M. E., (2) 589

- MORTON, A. A., Alfin-plus rubber. An extremely high molecular weight polymer, yet a compoundable rubber (Abstract), (2) 587
- , The formation of gel in Alfin-plus polymerization (Abstract), (5) 1332
- MORTON, M., see SANTEE, E. R., Jr., (5) 1156
- MUKHERJEE, D. P. AND C. GOLDSTEIN, A study of mechanical and optical properties of an alternating NBR and an emulsion NBR, (5) 1264
- MULLINS, L., see BRISTOW, G. M., (2) 555
- MURAKAMI, K., see KUSANO, T., (2) 388
- , see TAMURA, S., (2) 477
- MUZSHAY, I., see LENGYEL, V., (2) 581
- NAIR, S., see SIN, S. W., (2) 583
- NAKAJIMA, N., H. H. BOWERMAN, AND E. A. COLLINS, Viscoelastic behavior of butadiene-acrylonitrile copolymers at small and large deformations and their ultimate properties, (2) 417
- NAPLES, F. J., see MEYER, G. E., (1) 106
- NEFF, H. F., see MOGHE, S. R., (1) 286
- NIKOLSKII, V. G., see ZLATKEVICH, L. Yu., (5) 1210
- NOMURA, A., A. UEDO, Y. TODANI, AND K. KOMURO, Tensile properties of poly(isoprene) (Abstract), (2) 558
- NOVAJRA, G., see CARBONARO, A., (5) 1274
- NOVIKOVA, G. E., see MAREI, A. I., (2) 559
- OFSTEAD, E. A., Polypentenamer: effect of polymer microstructure on the equilibrium polymerization of cyclopentene (Abstract), (5) 1324
- OGDEN, R. W., Large deformation isotropic elasticity—on the correlation of theory and experiment for incompressible rubberlike solids, (2) 398
- O'GRADY, E. V., see BORSELLINO, J. V., (5) 1332
- OON, O. C., see SUNG, P. C., (2) 582
- ORLOV, V. A., On high strength bonding of SKI-3 based vulcanized rubber by cold setting adhesives (Abstract), (2) 580
- PAPE, P. G. AND H. F. STEWART, Rubber Modification with mercaptosilicones (Abstract), (2) 585
- PATEL, A. C. AND M. L. DEVINEY, Precision treadwear measurements at increased mileages by an improved radioiodine method, (4) 787
- PATEL, S. M., R. A. HIVELEY, AND J. O. COLE, Identification of accelerators in vulcanized rubber stocks by gas chromatography (Abstract), (5) 1325
- PEARSON, C. J., see HOGAN, J. M., (5) 1328
- PEKLO, M. J. P., see MORRISSEY, R. T., (5) 1331
- PENDLETON, J. F., see FALK, J. C., (4) 1044
- PETROVA, G. P., see MAREI, A. I., (2) 559
- PICKWELL, R. J., see SOLLMAN, K. J., (2) 584
- PIOTROVSKII, K. B., The ways for increasing cis-1, 4-poly(isoprene) stability (Abstract), (2) 569
- PLISKIN, I., Observations of the die swell behavior of filled elastomers measured automatically with a new die swell tester, (5) 1218
- , see TOKITA, N., (5) 1166
- POLYAK, M. A., N. B. CERNYAK, N. D. ZAKHAROV, AND G. I. KOSTRYKINA, Effect of elevated cure temperature on the structural parameters of vulcanization networks in isoprene rubbers (Abstract), (2) 566
- PODDUBNYI, I. YA., V. A. GRECHANOVSKII, AND L. S. IVANOVA, Molecular structure and macroscopic properties of synthetic poly(isoprene) (Abstract), (2) 556
- , see GRECHNOVSKII, V. A., (5) 1256
- POJARKOVA, A. D., see BUIKO, G. N., (2) 573
- POTTS, K. T., see D'AMICO, J. J., (5) 1299
- PUTYATINA, Z. P., see THOFIMOVICH, D. P., (2) 580
- PYNE, J. R., see HUMPHIDGE, R. T., (1) 148
- RAILSBACK, H. E., see SNAVELY, K. E., (5) 1324
- RAKOWSKY, K., P. ANACHKOV, V. JANAKIEW, AND P. GENCHEVA, Investigation of structural changes of unfilled and filled with active fillers cis 1, 4-(SKI-3) based compounds depending on processing conditions (Abstract), (2) 570
- RANNEY, M. W., see SOLLMAN, K. J., (2) 584
- RIVIN, D. AND R. G. TRUE, Filler reinforcement of liquid elastomers, (1) 161

- ROBERTS, R. W., H. L. STEPHENS, AND D. S. WINKLER, Extrusion drying of starch—elastomer masterbatches (Abstract), (2) 591
- ROBINSON, K. J., see BLACKSHAW, G. C., (5) 1324
- RODGER, E. R., see DAVIES, J. R., (2) 574
- RODGERS, W. A., Tension tests with cut ring specimens (Abstract), (2) 586
- ROGERS, T. H., see HOGAN, J. M., (5) 1328
- RUSCH, K. C. AND J. M. SLESSOR, An elastomeric impact-absorbing bumper system, (4) 862
- RUSSELL, C. R., see ABBOTT, T. P., (2) 590
- RYDER, D. F., see IYENGAR, Y., (2) 442
- SALAZER, E. A., see CURRO, J. G., (2) 530
- SALTMAN, W. M. AND L. J. KUZMA, Preparation and properties of polydienes, (4) 1055
- SANTEÉ, E. R., JR., L. O. MALOTKY, AND M. MORTON, Analysis of chain unit structure of poly(butadiene) by means of HR-300 spectrometer, (5) 1156
- SAPRONOV, V. A., Experience in using synthetic poly(isoprene) in the production of rubber articles (Abstract), (2) 563
- SCHAEFER, J., Comparisons of the carbon-13 nuclear magnetic resonance spectra of some solid cis and trans poly(isoprene)s, (2) 359
- , S. H. CHIN, AND S. I. WEISSMAN, Magic angle carbon-13 nuclear magnetic resonance spectra of filled rubber, (5) 1127
- SCHLOTT, R. J., see FALK, J. C., (4) 1044
- SCHWARZ, H. F., see BYRNE, P. S., (2) 591
- SCOTT, C. E., see ULMER, J. D., (4) 897
- SEKHAR, B. C., Review of developments in production, processing, and use of natural rubber (Abstract), (2) 581
- SHELTON, J. R., see COLEMAN, M. M., (4) 938, 957
- SHEPELOV, M. I., see CHERNAYA, V. V., (2) 566
- SHEUNG, S. C., see LEVINSON, M., (1) 294
- SHIH, H., AND P. J. FLORY, Equation of state parameters for poly(dimethylsiloxane), (2) 331
- , see FLORY, P. J., (2) 338
- SIN, S. W. AND S. NAIR, New concepts in the standardization and control of SMR (Abstract), (2) 583
- SINGH, A., see VIAL, T. M., (5) 1328
- SIRCAR, A. K. AND T. G. LAMOND, Carbon black transfer in blends of cis poly(butadiene) with other elastomers, (1) 178
- SIMPSON, B. D., see KLYNE, R. A., (1) 192
- SLESSOR, J. M., see RUSCH, K. C., (4) 862
- SMITH, D. J., see BORSSELLINO, J. V., (5) 1332
- SMITH, R. W., see FOLT, V. L., (5) 1193
- SNAVELY, K. E., T. R. WILSON, AND H. E. RAILSBACK, Butadiene-styrene block copolymer technology (Abstract), (5) 1324
- SOLLMAN, K. J., M. W. RANNEY, AND R. J. PICKWELL, Silane coupling agents—reduction of heat generation in mineral filled elastomers (Abstract), (2) 584
- SOMMER, J. G. AND D. A. MEYER, Factors controlling the dynamic properties of elastomeric products (Abstract), (5) 1330
- SON, P. N., Some observations on the mechanism of cure retardation, (4) 999
- SORG, E. H., see BORSSELLINO, J. V., (5) 1332
- STACY, C. J. AND R. L. ARNETT, Unperturbed polymer chain dimensions from intrinsic viscosities determined in good solvents, (2) 470
- STAVAROVA, A., see FIEDLER, A., (2) 579
- STENBERG, B. AND J. F. JANSSON, A compression relaxometer for rubber materials, (5) 1316
- STEPHENS, H. L., see BACSFALVI, V., (2) 588
- , see ROBERTS, R. W., (2) 591
- STEWART, H. F., see PAPE, P. G., (2) 585
- STRUCKER, N. E., see BEREJKA, A. J., (2) 590
- STUDEBAKER, M. L., see KLYNE, R. A., (1) 192
- SULLIVAN, A. B., see MORITA, E., (1) 67
- , see D'AMICO, J. J., (5) 1299
- SUNG, C. P. AND O. C. OON, Processing innovations in natural rubber (Abstract), (2) 582
- TAKEUCHI, M., see ALAKI, Y., (2) 350
- TAMURA, S. AND K. MURAKAMI, The determination of network chain density and the chemical stress relaxation of crosslinked polymers, (2) 477
- TAYLOR, G. L., see DAVISON, S., (1) 30
- THOMPSON, D. C., see ARNOLD, R. G., (3) 619

- TITOV, V. V., AND B. K. KARMIN, Specific features of tensile and elastic properties of pure gum vulcanizates based on isoprene rubbers with different microstructure (Abstract), (2) 560
- TRACHENKO, G. T., see MAREI, A. I., (2) 559
- TODANI, Y., see NOMURA, A., (2) 558
- TOKITA, N. AND I. PLISKIN, The dependence of processability on molecular weight distribution of elastomers, (5) 1166
- TREXLER, H. E., The formulation of nonburning elastomer compounds, (4) 1114
- TROFIMOVICH, D. P., L. P. GUSTOVA, I. A. ELKINA, AND Z. P. PUTYATINA, Application of cis-1, 4-poly(isoprene) dispersion in manufacture of foam rubber dipped goods and rubber treads (Abstract), (2) 580
- TRUE, R. G., see RIVIN, D., (1) 161
- TUCKER, R. G., see KRISHEN, A., (5) 1326
- TURNER, R. R., D. W. CARLSON, AND A. G. ALTENAU, Determination of ungrafted rubber in ABS polymers (Abstract), (5) 1327
- UEDO, A., see NOMURA, A., (2) 558
- ULMER, J. D., V. E. CHIRICO, AND C. E. SCOTT, The effect of carbon black type on the dynamic properties of natural rubber, (4) 897
- URBAN, E., see HESS, W. M., (1) 204
- VEITH, A. G., Accelerated tire wear under controlled conditions. I. Description of the test system, (4) 801
- , Accelerated tire wear under controlled conditions. II. Some factors that influence tire wear, (4) 821
- VER STRATE, G., see GARDNER, I. J., (4) 1019
- , E. N. KRESGE, AND C. COZEWITH, Polymerization control of structure and properties of ethene-propene elastomers (Abstract), (5) 1322
- VIAL, T. M. AND A. SINGH, Acrylic elastomers for automotive use—high temperature testing (Abstract), (5) 1328
- VINOGRADOVA, T. I., see FEDYUKIN, D. L., (2) 511
- WALROD, D. H., see HARPELL, G. A., (4) 1007
- WEISSMAN, S. I., see SCHAEFER, J., (5) 1127
- WESTFAHL, J. C., Electron spin resonance study of phenolic antioxidants. II. Free radical structures arising from antioxidants containing the 3, 5-di-tert-butyl-4-hydroxybenzyl group, (5) 1134
- WELLER, P. A., Urethane energy absorbers for automobile bumpers, (4) 843
- WHITE, J. R., see HOGAN, J. M., (5) 1328
- WHITTINGTON, W. H., see WOODS, M. E., (2) 589; (5) 1334
- WILKES, C. E., see MORRISSEY, R. T., (5) 1331
- WILLETT, P. R., Hysteretic losses in rolling tires, (2) 425
- WILLIAMS, M. L., see DEVRIES, K. L., (2) 540
- WILSON, T. R., see SNAVELY, K. E., (5) 1324
- WIMS, A. W., see MYERS, M. E., JR., (2) 464
- WINKLER, D. S., see ROBERTS, R. W., (2) 591
- WOLF, G. M., AND E. P. DE PALMA, Painted and color-pigmented elastomerics for bumper stone deflectors (Abstract), (5) 1325
- WOOD, L. A., Modulus of natural rubber crosslinked by dicumyl peroxide. II. Comparison with theory, (5) 1287
- WOODS, M. E., R. J. MORSEK, AND W. H. WHITTINGTON, Powdered rubber technology. IV. Recent advances in powdered nitrile elastomers (Abstract), (2) 589
- , AND W. H. WHITTINGTON, Powdered rubber technology. V. Economic analysis of the processing of powdered rubber compounds (Abstract), (5) 1334
- YOSHIMOTO, T., see ALAKI, Y., (2) 350
- ZAMBONI, V., see CARBONARO, A., (5) 1274
- ZAPP, R. L., Chlorobutyl convulcanization chemistry and interfacial elastomer bonding, (1) 251
- ZHAKAROV, N. D., see POLYAK, M. A., (2) 566
- ZHAKOVA, V. D., see KOPEMAN, L. S., (2) 557
- ZLATKEVICH, L. YU. AND V. G. NIKOLSKII, Dependence of the glass transition temperature on the composition of elastomer mixtures; (5) 1210
- ZOLOTAREVSKAYA, L. K., A. M. LIPKIN, A. E. GRINBERG, AND L. G. ANGERT, 1, 1, 4-Derivatives of Thiosemicarbazide—new non-staining antiozonants, (2) 517

SUBJECT INDEX

- Abrasion resistance, see also Tire wear controlled conditions, (4) 801, 821
new technology carbon blacks, (5) 1239
radioiodine method, (4) 787
- ABS polymers, see poly(acrylonitrile co butadiene co styrene)
- Abstracts, papers presented at the International Symposium on Isoprene Rubber—Moscow, (3) 555
papers presented at meetings of the Rubber Division, (3) 584; (5) 1321
- Accelerators of sulfur vulcanization, analysis by gas chromatography, (5) 1325-1326
cycloalkylthioamines, (1) 67
cycloalkylthio-3-azabicyclo (3,2,2) nonane, (1) 47
cyclohexylthiomethylpiperidines, (1) 47
cyclohexylthiopiperidines, (1) 47
cyclohexylthiopyrrolidines, (1) 47
effect on crosslink density, (2) 504
effect on rubber—cord adhesion, (4) 981
effect on vulcanization rate, (2) 504; (5) 1299
electron spin resonance spectroscopy of, (4) 938, 957
fragmentation in mass spectrometer, (5) 1299
mass spectral patterns of various, (1) 47; (5) 1299
nuclear magnetic resonance data of, (5) 1299
preparation of, (1) 67; (5) 1299
Raman spectroscopy of, (4) 938, 957
reaction mechanisms of, (2) 524; (4) 938, 957
rubber—bound intermediate, (4) 938
in vulcanizates, (4) 1035
identification by mass spectrometry, (1) 67; (4) 1035; (5) 1299
- Acrylic acid, N-(4-anilinophenyl) amide of, polymerizable antioxidant, (1) 96
preparation of, (1) 96
4-anilinophenyl ester of, polymerizable antioxidant, (1) 96
preparation of, (1) 96
3,5-di-t-butyl-4-hydroxyphenyl ester of, polymerizable antioxidant (1) 96
preparation of, (1) 96
- Acrylic rubber, see Poly (acrylate)
- Activator of sulfur vulcanization, (4) 938
reaction with accelerator, (4) 938
- Acyl halides, fluorinated, elastomers from, (3) 619
- Adhesion, aging and, (1) 251
covulcanization and, (1) 251
of Chlorobutyl rubber, (1) 251
effect of crosslink structure on, (1) 251
improved by radio-frequency-activated (2) 549
of poly (butadiene co styrene) rubber, (1) 251
rubber—cord, (2) 442; (4) 981
effect of accelerators, (4) 981
effect of antioxidant, (4) 981
effect of bonding agent, (4) 981
effect of retarders, (4) 981
effect of scorch time, (4) 981
effect of sulfur concentration, (4) 981
polyester tire cord, (4) 981
steel cord, (4) 981
textile cord, (4) 981
between rubber interfaces, (1) 251
test for rubber—metal adhesion, (4) 862
- Aging, effect on interfacial adhesion of rubber by, (1) 251
effect on natural rubber by thiosemicarbazides, (2) 517
high temperature, of poly (acrylates), (5) 1328
of poly (butadiene co acrylonitrile), (2) 483
mechanisms in poly (butadiene co acrylonitrile), (2) 483
- Alfin rubbers, (2) 587; (5) 1332
- Alfrey-Goldfinger equation, use for reactivity ratios, (1) 30
- Allyl ethers, elastomers from fluorinated, (3) 619
- Alternating copolymers, poly (butadiene co acrylonitrile), (5) 1264
poly (isobutylene co ethyl acrylate), amine curable, (4) 1068
oil resistance of, (4) 1068
sulfur curable, (4) 1068
solubility parameter, (4) 1068
water resistance, (4) 1068
poly (isobutylene co methyl acrylate), (4) 1068
poly (styrene co acrylonitrile), (4) 1068
properties of, (4) 1068
poly (styrene co methyl acrylate), (4) 1068
glass transition temperature, (4) 1068
poly (styrene co methyl methacrylate), (4) 1068
glass transition temperature of, (4) 1068
- Aluminum ethoxide, scorch control of vulcanization by, (1) 78
- Aluminum isopropoxide, scorch control of vulcanization by, (1) 78
- Amines, as curing agents for fluoroelastomers, (3) 619
- Amine complexes of zinc bis (dimethyldithiocarbamate), (2) 524; (4) 938
- Amino acids, content of protein in natural rubber, (1) 47

- Analysis, accelerators by gas chromatography, (5) 1325
of airborne tire dusts, (1) 232
of copolymer compositional variation with molecular weight, (2) 449
of interfacial bonding of rubbers, (1) 251
Antimony oxide, in nonburning elastomer-compounds, (4) 1114
Antioxidants, activity of polymerizable antioxidants as, (1) 96
amine, polymerizable, (1) 96
4-anilinodiphenyl esters, (1) 96
preparation of, (1) 96
chemically attached, (1) 96, 106
deuterated, (5) 1134
di-*t*-butyl-4-hydroxyphenyl, (1) 96
preparation of, (1) 96
effect on aging of poly (butadiene co acrylonitrile), (2) 483
effect on cure of poly (ethylene co propylene co diene), (4) 1007
effect on rubber-cord adhesion, (4) 981
effect on scorch time, (4) 981
effect on stress relaxation of poly (acrylates), (5) 1328
for emulsion rubbers, (1) 96
electron spin resonance spectra of, (5) 1134
mechanisms of reactions of, (5) 1134
non-extractable, polymerizable, (1) 106
non-staining, polymerizable, (1) 106
non-volatile, polymerizable, (1) 106
phenolic, polymerizable, (1) 96
primary radicals in, (5) 1134
radical stability of (5) 1334
reaction intermediates, (5) 1134
Antioxonants, non-staining, (2) 517
preparation of, (2) 517
Apparatus, for compression, (5) 1316
for creep measurement, (4) 1077
cure controller simulator, (4) 1103
application to operational problems, (4) 1103
cooling of rubber slabs, (4) 1103
on-line cure simulation, (4) 1103
die-swell tester, (5) 1218
for mixing liquid rubbers, (1) 148
for repeated stress relaxation test, (2) 388
Aziridine, (4,4'-methylene) bis, as vulcanizing agent for liquid rubber, (1) 139

Balata, see *trans* Poly (isoprene)
Barium sulfate, filler for fluoroelastomers, (3) 619
in microscopy of vulcanizates, (3) 653
Benzene, equation-of-state parameters for, (2) 338
Benzoethiazolinethione, scorch inhibitor for thiuram vulcanization, (2) 504
Biographical sketches, Collins, A. M., (2) G45
Dannenber, E. M., (1) G7
Newton, E. B., (4) G80
Birefringence, measure of, (3) 653
in stretched natural rubber, (3) 653
of poly (butadiene co acrylonitrile), (5) 1264
Blends, carbon black distribution in, (3) 653
Chlorobutyl and poly (butadiene), (1) 251
Chlorobutyl and poly (butadiene co styrene), (1) 251
crosslink structure in, (1) 251
electron microscopy of, (5) 1193
interfacial bonding of, (1) 251
effect of curing recipe on, (1) 251
measure of, (1) 251
microscopy of, (3) 653
rheology of, (5) 1193
transfer of carbon black between phases of, (1) 178
Block copolymers, (1) 242; (4) 1044, 1087
properties of poly (butadiene co acrylonitrile), (1) 242
poly (butadiene co styrene), (1) 242
poly (styrene co butadiene co styrene), (1) 242
radial, (2) 588
Bonding, see also Adhesion
with basic accelerators, (4) 981
compounds for, (4) 981
with different sulfenamides, (4) 981
formulation of, (4) 981
room temperature vulcanization, (2) 580
rubber-cord, (4) 981
Bound rubber, effect on properties, (2) 570
microscopy of, (3) 653
Braebender Plastograph, (5) 1193
Bromobutyl rubber, vulcanization of, (5) 1334
Butyl rubber see also Poly (butylene co isoprene) flammability, (4) 1114
liquid, in rubber compounding, (2) 590
poly (styrene) graft in, (4) 1044

Calcium carbonate, filler for fluoroelastomers, (3) 619
in vulcanizates, microscopy of, (3) 653
Calcium oxide, in fluoroelastomer vulcanizates, (3) 619
Calendering, of fluoroelastomers, (3) 619
Carbon-13 nuclear magnetic resonance spectroscopy, poly (butadiene), (2) 350, 359
carbon atom structure and, (2) 350
line intensities in, (2) 250
microstructure and spectral line assignment, (2) 350
sequence distribution of microstructure, (2) 350
poly (isoprene)
carbon atom location and line assignment, (2) 359; (5) 1126
cis and trans, (2) 359
effect of carbon black, (2) 359; (5) 1126
enhancement of, (2) 359
high- and low-frequency segmental motion, (2) 359
line width of, (2) 359
new spectral line of carbon black-poly (isoprene) mixture, (5) 1126
Overhauser enhancement, (2) 359

- spin-lattice relaxation times, (2) 359
- spinning of sample at magic angle and line narrowing, (5) 1126
- Carbon-14 tagged, ethylenenorbornene, (4) 1019
 - poly (ethylene co propylene co butene), (1) 30
- Carbon black, DBP number, iodine number, and tint, (4) 821
- dispersion in liquid elastomers, (1) 148
- dispersion measurement by microscopy, (3) 653
- distribution in blends, (1)¹ 178; (3) 653
- effect of concentration on crystallization of poly (butadiene), (1) 178
- effect on elastomer breakdown during milling, (5) 1218
- effect on green strength of poly (isoprene)s, (5) 1234
- effect on interfacial adhesion of rubbers, (1) 251
- effect on rubber relaxation time, (5) 1218
- effect of structure on elastic modulus, (4) 897
- effect of type on dynamic properties, (4) 897
 - on mixing procedure, (4) 897
- electron micrographs, (5) 1239
- in fluoroelastomers, (3) 619
- graphitized, (4) 877
- HAF, morphology of, (1) 204
- identification by microscopy, (3) 653
- influence on carbon-13 NMR spectrum of poly (isoprene), (2) 359
- interaction with poly (isoprene), (5) 1234
- light scattering by, (3) 653
- low angle x-ray studies of, (2) 588
- during mastication of rubbers, (3) 653
- microstructure in rubbers, (3) 653
- migration of, in blends of Chlorobutyl and poly (butadiene), (1) 204
- morphology, by image analysis computer, (1) 204
- new technology, (5) 1239
- particle size, (3) 653
 - by x ray, (2) 588
- quantitative determination by microscopy, (3) 653
- reinforcement of liquid elastomers, (1) 161
- road wear of rubber reinforced by, (5) 1239
- shape classification of primary units, (1) 204
- shape effect on tire wear, (1) 178
- shape image analysis, (1) 204
- Stokes diameter, (5) 1239
- structure, (5) 1239
- surface areas of, (1) 192
 - and porosity, (5) 1239
 - and structure, (4) 897
- surface area tests, CTAB absorption, (1) 192
 - electron microscope, (1) 192
 - reflectance, (1) 192
 - "t", (5) 1239
- tinting strength, (5) 1239
- transfer of, in elastomer blends, (1) 178
- variation of dispersion with mixing time, (5) 1218
- Capillary flow, of blends, (5) 1193
 - of poly (butadiene co acrylonitrile), (2) 417
- Capillary rheometer, (2) 417; (5) 1193
- Carboxylated poly (isoprene), (1) 47
- Carboxylic rubbers, scorch control, (1) 78
- Caulks, from fluoroelastomers, (3) 619
- Chain dimensions, from intrinsic viscosity, (2) 470
 - Stockmayer-Fixman equation, (2) 470
- Chain entanglement, (2) 359, 477
 - molecular weight between, (2) 477
- Chain extension, liquid elastomers, (1) 139
- Chain transfer in copolymerization of vinylidene fluoride, (3) 619
- Chemorheology under mechanical strain, (2) 388
- Chlorinated poly(ethylene), compounding, (5) 1336
- Chlorobenzene, equation-of-state for, (2) 338
- Chlorobutyl rubber, analysis by gas chromatography, (5) 1326
 - covulcanized with diene rubbers, (1) 251
 - dynamic mechanical properties, (5) 1330
- Chloroprene, see Poly (chlorobutadiene)
- Chlorowax, in nonburning compounds, (4) 1114
- Chromatography, gas-liquid, (1) 1, 7, 14
 - of pyrolyzates of airborne tire dusts, (1) 232
- Chromatography, gel permeation, (1) 115
 - diffusion in, (1) 115
 - copolymer analysis as function of molecular weight, (2) 449
 - measure of oil in oil-extended rubber, (2) 449
- Cinnamate, 3,5-di-t-butyl-4-hydroxyphenyl ester, polymerizable antioxidant, (1) 96
 - preparation of, (1) 96
- 4-anilinophenyl ester, polymerizable antioxidant, (1) 96
 - preparation of, (1) 96
- Clay, in vulcanizates, microscopy, (3) 653
- Collagen, energetic contribution to elastic force, (3) 593
 - temperature coefficient of unperturbed dimensions, (3) 593
- Collins, Arnold M., biographical address, (2) G45
- Comonomer distribution in copolymers, (2) 449
- Compatiability of polymers, (3) 653; (5) 1188, 1193
- Complexed copolymerization, (4) 1068
 - alternating copolymers from, (4) 1068
- Compliance, (5) 1166
- Compressibility, influence on compression modulus, (1) 286
 - of poly (dimethylsiloxane), (2) 331
- Compression modulus, apparatus for measuring, (5) 1316
 - dependence on Poisson's ratio, (1) 285

- Compression relaxation, effects of compound-
ing variations, (1) 305
- Compression set, effects of temperature, (1)
305
of fluoroelastomer vulcanizates, (3) 619
influence of cure system, (1) 305
of poly (butadiene co acrylonitrile), (1) 305
of poly (isoprene), (2) 555
- Computers, in compound development, (2)
587
- Conductivity, electrical, of rubber blends, (1)
178
- Configurational sequence structure of poly
(butadiene)s, (2) 350
- Constitutive equations, of three layered
cylindrical shell, (1) 294
- Covulcanization, of Chlorobutyl and poly
(butadiene), (1) 251
- Crosslinking, see also Vulcanization
of aged poly (butadiene co acrylonitrile),
(2) 483
effect of antioxidant, (2) 483
effect of crosslink structure, (2) 483
effect of vulcanization by products, (2) 483
by ionizing radiation, (1) 30
- Crotonate, 3,5-di-*t*-butyl-4-hydroxyphenyl,
polymerizable antioxidant, (1) 96
preparation of, (1) 96
- Creep, apparatus for, (4) 1077
compliance of vulcanizates, (4) 1077
compliance curve, (4) 1077
equations, (4) 1077
of poly (isoprene), (2) 555
- Crosslink, effect of type on interfacial bond-
ing of rubber blends, (1) 251
- Crosslink density, effect of high temperature
vulcanization, (2) 566
- Crystallinity, in alpha olefin polymers, (1) 30
determination by gas chromatography, (1)
7
of natural rubber by microscopy, (3) 653
by NMR, (1) 22
- Crystallization, determination of polymer
compatibility by, (1) 178
effect of carbon black on elastomer, (1) 178
effect of poly (butadiene co styrene) on
poly (butadiene), (1) 178
minimum sequence length for, (1) 30
of poly (isoprene)s, (1) 22; (2) 559
stress-induced, (5) 1274
- Crystallization kinetics, comparison of meth-
ods of determination, (1) 14
by gas chromatography, (1) 14
from NMR spectra, (1) 22
of *cis* poly (isoprene), (1) 22
of *trans* poly (isoprene), (5) 1331
- Curative dispersion, effects of, (2) 511
- Cure rate, Braebender curves, (4) 999
Curometer, (4) 999, 1007
control, (4) 1103
effect of retarders, (4) 999
heat flow and, (4) 1103
kinetic parameter, (4) 999
- Curing agents for fluoroelastomers, (3) 619
- Cycloalkylthioamines, as accelerators and
prevulcanization inhibitors, (1) 67
- Cyclohexane, equation-of-state parameters
for, (2) 338
- Cyclohexyldithiobenzimidazole and deriva-
tives, accelerator activity, (5) 1299
mass spectral fragmentation pattern, (5)
1299
- NMR data, (5) 1299
preparation of, (5) 1299
as retarders, (5) 1299
- Cyclohexyldithiobenzothiazole and deriva-
tives, as accelerators, (5) 1299
mass spectral fragmentation patterns, (5)
1299
NMR data, (5) 1299
preparation of, (5) 1299
- Cyclohexyldithiobenzoxazole and derivatives,
accelerator activity of, (5) 1299
mass spectral fragmentation patterns, (5)
1299
NMR data, (5) 1299
preparation of, (5) 1299
as retarders, (5) 1299
- Cyclohexyldithio-4-methylthiazoles and de-
rivatives, as accelerators, (5) 1299
mass spectral fragmentation patterns, (5)
1299
NMR data, (5) 1299
preparation of, (5) 1299
- Cyclohexylthioamines, accelerators, (1) 67
- Cyclohexylthiomethylpiperidines, accelera-
tors of sulfur vulcanization, (1) 67
- N-Cyclohexylthiophthalimide, comparison
with cycloalkylthioamines as prevulcan-
ization inhibitors, (1) 67
- Cyclohexylthiopiperidines, as accelerators of
sulfur vulcanization, (1) 617
- Cylinders, rubber, deformation of, (2) 530
- Deformation index, (5) 1166
diagram, (5) 1166
poly (butadiene), (5) 1166
- Degradation, mechanical of rubber, (2) 388
- Density, poly (dimethylsiloxane), (2) 331
- 1-6-Diaminohexane, as curing agent for flu-
oroelastomers, (3) 619
crosslinking agent for poly (butadiene co
vinylpyridine), (5) 1285
- 2-6-Di-*t*-butyl-*p*-cresol derivatives, ESR spec-
tra of, (5) 1134
mechanism of radical degradation, (5) 1134
radical reactions of, (5) 1134
- 3,5-Di-*t*-butyl-4-hydroxybenzyl derivatives,
ESR spectra of, (5) 1134
primary radicals in, (5) 1134
- N, N'-Dicinnamylidene-1,6-diaminohexane,
as curing agent for fluoroelastomers, (3)
619
- N, N'-Dicinnamylidene-1, 6-diaminohexane,
as curing agent for fluoroelastomers, (3)
619
- Dicyclohexylthiopiperazine, as accelerator of
sulfur vulcanization, (1) 67

- Die swell, definition, (5) 1218
 effect of black structure, (5) 1218
 effect of carbon black, (5) 1218
 effect of mechanical cleavage of rubber on, (5) 1218
 effect of molecular weight distribution on, (5) 8
 equations for, (5) 1218
 variation with filler volume, (5) 1218
 of various elastomers, (5) 1218
 Differential scanning calorimetry, (1) 178
 Diffusion, configurational equations for, (1) 126
 of low molecular weight rubbers through membranes, (1) 115
 Dimethyl dimethylthiocarbamyl sulfenamide, (4) 938
 N, 4-Dinitroso-N-methylaniline, (2) 573
 as modifier for poly (isoprene), (2) 511
 Dispersion of curatives, effect on vulcanizate properties, (2) 511
 Disulfides, cyclohexyl benzothiazolyl, (5) 1299
 mass spectral fragmentation patterns, (5) 1299
 NMR data, (5) 1299
 preparation of, (5) 1299
 unsymmetrical, (5) 1299
 4, 8-Dodecadiene, 300 Mhz NMR, (5) 1156
 Dodecane, "molecular probe" for gas-liquid chromatography of polymers, (1) 1, 7
 Dust, atmospheric, from tire wear, (1) 232
 sampling method, (1) 232
 Dynamic properties, ADL ball rebound tester, (4) 1087
 Goodrich flexometer, (4) 897
 Goodyear-Healy rebound, (4) 897
 MTS elastomer test system, (4) 897
 Pirelli Hysteresimeter, (4) 897, 935
 of poly (butadiene co acrylonitrile), (2) 417
 Rheovibron, (4) 1087
 Wallace dynamic tester, (4) 897
 Elastic recovery, (5) 1166
 Elastic modulus, effect of carbon black type, (4) 897
 effect of frequency, (4) 897
 effect of strain amplitude, (4) 877, 897
 effect of surface area and structure of black, (4) 897
 effect of temperature, (4) 897
 at low loading, (4) 877
 of natural rubber, (4) 897
 at normal loading, (4) 877
 of vulcanizates, effect of carbon black structure, (4) 877
 temperature-frequency transposition, (4) 877
 theory of, (4) 877
 Elasticity theory, mathematical, (2) 398
 molecular, (1) 127
 statistical, (5) 1287
 use in belted tire design, (1) 294
 Elastin, energetic contribution to elastic force, (3) 593
 temperature coefficient of unperturbed dimensions, (3) 593
 Electron micrographs, of carbon black, (1) 148, 178, 204; (3) 653; (4) 877, 897
 of fractured rubber surfaces, (3) 653
 of protein from natural rubber, (1) 47
 of vulcanizate section, (4) 877
 Electron microscope & carbon black morphology, (1) 204
 Electron microscopy, molecular weight by, (3) 653
 of rubbers, (3) 653
 Electron spin resonance spectra, of accelerators, (4) 938
 of antioxidants, (5) 1134
 in ozone cracking studies, (2) 540
 of thermal decomposition of accelerators, (4) 957
 of vulcanizing systems, (4) 957
 Elongation, effect on milling of elastomers, (5) 1166
 effect of stress, (5) 1234
 equation as a function of temperature, (2) 388
 poly (butadiene co acrylonitrile), (2) 417
 relationship, to glass transition, (1) 242
 to melting temperature, (1) 242
 temperature dependence, (1) 242
 temperature of maximum, (1) 242
 ultimate, of vulcanizates, (1) 242
 Emulsion rubbers, copolymerized with polymerizable antioxidants, (1) 106
 Energetic contribution to elastic force, measurement, (3) 593
 molecular interpretations, (3) 593
 thermodynamics of, (3) 593
 from thermoelasticity, (3) 593
 Energy absorbers, for automobile bumpers, (4) 843, 862
 designs, (4) 862
 effect of compliance, (4) 843
 effect of form factor, (4) 843
 effect of loading, (4) 843
 effect of stroke, (4) 843
 recipe for natural rubber, (4) 862
 telescope system for, (4) 843
 tester for, (4) 862
 Energy, activation, for viscous flow, (1) 161
 internal, of polymer chains, (1) 126
 temperature dependence, (1) 126
 Energy consumption, frictional losses between tires and roads, (2) 425
 of rolling tires, (2) 425
 Energy density, breaking, (5) 1166
 equations for, (5) 1166
 Energy, dissociation of hydrogen from hydrocarbons, (4) 1007
 Enthalpy, adsorption of dodecane on polymers, (1) 1
 mixing of dodecane with polymers, (1) 1
 Entropy, component of shear modulus of natural rubber, (5) 1287
 EPDM, see poly (ethylene co propylene co diene)
 EPM, see poly (ethylene co propylene)

- Epichlorhydrin-ethylene oxide rubber, (2) 587
- Epichlorhydrin rubber, aging, (4) 927
- filler effect, (4) 927
- flammability, (4) 1114
- Equation-of-state parameters, (2) 331
- Equibiaxial tension, (2) 398
- Ethylidenenorbornene, analysis of in poly (ethylene co propylene co diene), (4) 1019
- carbon-14 tagged, (4) 1019
- as diene termonomer in poly (ethylene co propylene co diene), (4) 1019
- radioassay, (4) 1019
- Extrusion, of vinylidene fluoride copolymers, (3) 619
- Factice, identification in rubbers, (3) 653
- Fillers, for fluoroelastomers, (3) 619
- identification in vulcanizates, (3) 653
- microscopy of, in vulcanizates, (3) 653
- Flammability, of elastomeric compounds, (4) 1114
- formulation of, (4) 1114
- tests, (4) 1114
- Flame retardant additives, (4) 1114
- Flexure of layered orthotropic shells, as related to belted tire, (1) 294
- Flow of elastomers, (5) 1166
- of elastomer blends, (5) 1166
- Fluoroelastomers, applications, (3) 619
- effect of fillers, (3) 619
- monomers for, (3) 619
- preparation, (3) 619
- processing, (3) 619
- properties, (3) 619
- review of, (3) 619
- Viton A, flammability, (4) 1114
- vulcanizate properties, (3) 619
- vulcanization, (3) 619
- Fluorolefins, elastomers from, (3) 619
- Fluorosilicone elastomers, effect of fillers, (3) 619
- flammability, (4) 1114
- as plasticizers for fluoroelastomers, (3) 619
- preparation, (3) 619
- properties, (3) 619
- vulcanization, (3) 619
- Fokker-Planck equation, application, (1) 127
- Fracture of rubbers, microscopical examinations, (3) 653
- Friction factor, calculation for polymer molecules, (1) 127
- Gas chromatography, of amino acid derivatives from protein in natural rubber, (1) 47
- analysis of accelerators by, (5) 1325
- pyrolyzates of polymers, (5) 1326
- Gas chromatography, polymers as liquid phase, (1) 1, 7, 14
- determination of polymer crystallinity by, (1) 7
- determination of glass transition temperatures by, (1) 1
- determination of rates of crystallization by, (1) 14
- Gel permeation chromatography, (1) 115; (2) 449; (5) 1193
- analysis of monomer composition as function of molecular weight, in a single polymer, (2) 449
- analysis of oil content in polymers, (2) 449
- compared to membrane osmometry for number average molecular weight determination, (1) 115
- Glass transition, activation energy of, (5) 1264
- Glass transition temperatures, of alternating copolymers, (4) 1068
- poly (styrene co acrylonitrile), (4) 1068
- poly (styrene co methyl acrylate), (4) 1068
- poly (styrene co methyl methacrylate), (4) 1068
- from gas chromatographic studies of polymers as liquid phase, (1) 1
- measure by radiothermoluminescence, (5) 1210
- multiple, (5) 1210
- of poly (butadiene co acrylonitrile), effect of blending, (4) 1087
- effect of conversion, (4) 1087
- effect of crosslinker, (4) 1087
- effect of monomer ratio, (4) 1087
- relationship to temperature of maximum elongation, (1) 242
- variation with microstructure, of poly (butadiene), (5) 1166
- of poly (butadiene co styrene), (5) 1166
- Goodyear, Charles, medalist 1973—Arnold M. Collins, (2) G45
- address, (2) G48
- Graft polymers, of poly (styrene) to Butyl rubber, (4) 1044
- to cis poly (butadiene), (4) 1044
- to 1, 2-poly (butadiene), (4) 1044
- to poly (ethylene), (4) 1044
- to poly (ethylene co propylene), (4) 1044
- to poly (ethylene co propylene co diene), (4) 1044
- to poly (isoprene), (4) 1044
- tensile properties, (4) 1044
- thermoplastic elastomers, (4) 1044
- Griffith theory of failure, (2) 540
- Guide for authors, (3) G59
- Guth-Gold equation, (4) 877
- Gutta Percha, blends with poly (isoprene), (2) 571
- Heat flow, analog simulators for, (4) 1103
- by conduction through thermocouple, (4) 1103
- cooling of rubber slabs, (4) 1103
- cure control, (4) 1103
- geometrical effects, (4) 1103
- on-line monitoring, (4) 1103
- one-dimensional simulator, (4) 1103
- theory, (4) 1103
- two-dimensional simulator, (4) 1103

- Heat resistance of fluoroelastomers, (3) 619
 Heat resistant poly (butadiene co acrylonitrile)
 Hertz theory, (2) 530
 Hexamethylene diamine, curing agent for fluoroelastomers, (3) 619
 Hexamethylene diamine carbamate, curing agent for fluoroelastomers, (3) 619
 High temperature aging of poly (butadiene co acrylonitrile), (2) 483
 Hooke's law, application, (1) 294
 Hydrodynamic volume, see Gel permeation chromatography
 Hydroformylated poly (isoprene), (1) 47
 Hysteresis, of rolling tires, (2) 425
- Incompatibility of polymers, detected by microscopy, (3) 653
 detected by glass transition temperatures, (5) 1210
 detected by radiothermoluminescence, (5) 1210
 Identification of rubbers, by refractive index dispersion, (3) 653
 by pyrolyzates and gas chromatography, (5) 1326
 Infrared radiation, tire surface temperature by, (4) 821
 Infrared spectra, absorbance data for poly (α -olefins), (1) 30
 of accelerators, (4) 938
 of carboxylated poly (isoprene), (1) 47
 of hydroformylated poly (isoprene), (1) 47
 of natural rubber, (1) 47
 deproteinized, (1) 47
 of tetramethylthiuram tetrasulfide, (4) 938
 Injection molding, of liquid elastomers, (1) 148
 Interfacial elastomer bonding, detection by differential solvent swelling, (1) 251
 Interference microscopy of rubbers, (3) 653
 Intrinsic viscosity, in good solvents, (2) 470
 unperturbed dimensions of polymers from, (2) 470
 Iodine, radioactive, tire wear measurement by, (4) 787
- Kinetics of crystallization, (1) 14, 22
 comparison of NMR and x-ray methods, (1) 22
 Kinetic reactivity parameters, (1) 30
- Laser beam, Raman spectra, (4) 938, 957
 Latex, foam rubber technology, (2) 464
 maturation, (2) 464
 microscopy of, (3) 653
 particle-size distribution, (3) 653
 precure of, (2) 464
 treatment of fabrics by chemically attached antioxidant protected, (1) 106
 Lead azide, in fluoroelastomer vulcanization (3) 619
 Lead phosphite, in fluoroelastomer vulcanization, (3) 619
- Light scattering, by carbon black, (3) 653
 low angle, in latex technology, (2) 464
 Liquid rubber, carboxyl terminated poly (butadiene), (1) 139
 crosslinking of, (1) 161
 melamine-formaldehyde pigments for, (1) 161
 processing equipment for, (1) 148
 properties of, (1) 148
 reinforcement with fillers, (1) 161
 reinforcement with textile fibers, (1) 148
 rheology of, (1) 161
 vulcanization of, (1) 139
 Liquid rubber technology, (2) 589
- Magnesium oxide, in fluoroelastomer vulcanization, (3) 619
 microscopy of, in vulcanizates, (3) 653
 Mass spectrometry, of accelerators of sulfur vulcanization, (4) 1035; (5) 1299
 fragmentation patterns of unsymmetrical disulfides, (5) 1299
 sample cup design, (4) 1035
 Mastication of rubbers, carbon black role in, (3) 653
 hypothesis of, (3) 653
 investigation by microscopy, (3) 653
 Meetings, International rubber Conference at Prague, (1) G20
 Polymer Division, (1) G12
 Rubber Division, (1) G8; (4) G77
 Melamine-formaldehyde pigments for liquid elastomers, (1) 161
 Mercaptobenzothiazole, see Benzothiazoline-thione
 Mercaptopropylsiloxanes, as modifier of rubbers, (2) 585
 Mercaptopropylsilane, interfacial modifier in mineral-filled rubber, (2) 584
 Methacrylate, 3,5-di-*t*-butyl-4-hydroxyphenyl, polymerizable antioxidant, (1) 96
 preparation, (1) 96
 4-anilinophenyl, polymerizable antioxidant, (1) 96
 preparation, (1) 96
 Methyl iodide, effect on crosslinked poly (butadiene co acrylonitrile), (2) 483
 N-2-Methyl-2-nitropropyl-4-nitrosaniline, as prevulcanization crosslinkers for green strength of poly (isoprene), (2) 573, 574, 575
 Metalation of 1,5-polyenes, (4) 1044
 for styrene graft, (4) 1044
 Microscopy of rubbers, interference measurement, (3) 653
 phase contrast techniques, (3) 653
 review of, (3) 653
 technique, (3) 653
 Microstructure, by gas chromatography, (1) 1
 of poly (butadiene), (2) 350; (4) 1055; (5) 1156, 1264, 1274
 Microtoming of rubber specimens, (3) 653

- Mixing, of blends of elastomers, effect of order of mixing, (1) 178
- characteristics of elastomers, (5) 1166, 1188, 1193
- temperature function of, (5) 1193
- time function of, (5) 1193
- torque of, (5) 1188, 1193
- Modulus, compression, energy component of, (5) 1287
- change with crosslinking, (5) 1287
- entropy component of, (5) 1287
- experiment compared with theory equation for, (5) 1287
- as function of temperature, (5) 1287
- and gel point, (5) 1287
- test of theory of rubber elasticity, (5) 1287
- thermodynamical equations for, (5) 1287
- variation with crosslinking, (5) 1287
- Modulus, dynamic, black loaded poly (butadiene) rubbers, (1) 178
- elastic, and double strain amplitude, (1) 178
- and electrical conductivity, (1) 178
- Molding, of fluoroelastomers, (3) 619
- Molecular weight, and intrinsic viscosity, (2) 470
- Molecular weight, determination by electron microscopy, (3) 653
- Molecular weight, distribution of, in copolymers, (2) 449
- by gel permeation chromatography, (1) 115; (2) 449
- by membrane osmometry, (1) 115
- of polymer blends, (2) 449
- Molecular weight, number average, (1) 115; (5) 1166
- diffusion through membranes and, (1) 115
- Molecular weight, weight average, (5) 1166
- Mooney molecular theory, viscoelastic behavior, modified, (1) 127
- Mooney recoil, (5) 1166
- of poly (butadiene), (5) 1166
- Mooney-Rivlin equation, (2) 388, 483; (3) 593
- in thermoelastic measurements, (3) 593
- Mooney viscosity (torque), (5) 1166
- Morphology, of carbon black, (1) 204
- Natural rubber, aging of, (2) 504, 517; (4) 927
- birefringence, (3) 653
- blends, (3) 653
- carbon black distribution in, (3) 653
- carbonyl groups in, (1) 47
- chain entanglement, (1) 477
- measure of, (1) 477
- chain scission, (1) 477
- chemical stress relaxation, (1) 477
- chemorheology, (2) 388
- cohesion, effect of gel, (5) 1234
- comparison with synthetic poly (isoprene), (1) 47; (2) 555-583
- compatibility, (5) 1188
- compression modulus of gum vulcanizates, (1) 286; (5) 1287
- temperature dependence, theory and experiment, (5) 1287
- crosslink density, (2) 447; (5) 1287
- crystallization, effect of polar groups, (2) 559
- kinetics, (1) 22
- on stretching, (2) 556
- crystallinity by microscopy, (3) 653
- with cycloalkylthioamine acceleration, (1) 67
- deproteinized, (1) 47
- dicumyl peroxide cure, (5) 1287
- dynamic properties, (2) 561; (4) 897; (5) 1330
- effect of gel on, (5) 1234
- effects of naturally occurring non-rubber constituents in, (1) 47; (2) 556
- effect on poly (butadiene) crystallinity, (1) 178
- effect of protein content upon dissolution, (1) 47
- effect of sol, (5) 1234
- on green modulus, (5) 1234
- effect of thiosemicarbazides on properties, (2) 517
- electron microscopy, (3) 653; (5) 1193
- energetic contribution to elastic force, (3) 593
- equation-of-state parameters for, (2) 331
- filler effect, (4) 927
- flammability, (4) 1114
- flow, (5) 1188
- gel composition, (1) 47
- gel point of, (5) 1287
- gel permeation chromatography of, (5) 1193
- graft, poly (styrene), (4) 1044
- gum vulcanizates, (2) 560; (5) 1287
- for impact absorbers, (4) 862
- impurities in, (1) 47; (3) 653
- infrared spectra of, (1) 47
- latex, microscopy of, (3) 653
- particles in, (3) 653
- particle size distribution, (3) 653
- mechanism of cure retardation, (4) 999
- microscopy, (3) 653
- mixing, (5) 1193
- Modulus, (5) 1287
- function of temperature, (5) 1287
- molecular weight by electron microscopy, (3) 653
- non-staining antiozonants for, (2) 517
- ozone resistance, (2) 517
- peroxide cure, (2) 477; (5) 1287
- plasticization rate, (1) 47
- prevulcanization inhibition, (2) 504
- production processing, (2) 581
- protein content, (1) 47
- refractive index, (3) 653
- refractive index dispersion, (3) 653
- review of recent developments, (2) 581
- rheology of, (5) 1188, 1193
- rigid lattice hydrogen atoms in, (1) 22

- shear modulus of, (5) 1287
- equations for parameter variations, (5) 1287
- standardization, (2) 583
- stark rubber, (1) 22
- NMR spectrum of, (1) 22
- stress-optical coefficient, (3) 653
- stress relaxation, (1) 477; (5) 1316
- sulfur-free thiuram vulcanization, (2) 504
- temperature coefficient, of unperturbed dimensions, (3) 593
- of shear modulus, (5) 1287
- tensile of gum vulcanizates, (2) 580
- thermodynamics of, (5) 1287
- torque-blend function, (5) 1193
- wear of, (4) 787, 821
- zinc complexes in vulcanization, (2) 504
- Neoprene, see Poly (chlorobutadiene)
- Network structure, changes during aging, (2) 483
- Nitrile rubber, see Poly (butadiene co acrylonitrile)
- p-Nitrosodiphenylamine, green strength improver, (2) 575
- Nuclear magnetic resonance, carbon-13, (2) 350
- data for unsymmetrical disulfides, (5) 1299
- determination of ethyldienenorbornene in poly (ethylene co propylene co diene) rubber, (4) 1019
- and kinetics of crystallization, (1) 22
- spectra of poly (butadiene), (2) 350; (5) 1156
- of poly (isoprenes), (2) 359; (5) 1127
- Nylon tire cord, adhesion to rubber, (4) 981
- bonding agent for, (4) 981
- effect of accelerators, (4) 981
- effect of sulfur concentration, (4) 981
- Obituary—Edwin B. Newton, (4) G80
- Oil-extended poly (butadiene co styrene), molecular weight distribution of, (2) 449
- measure of oil content by gel permeation chromatography, (2) 449
- Olefin terpolymers, sequence length distribution, (1) 30
- O-rings, bulge, mathematics of, (2) 530
- elastic solution for small deformation, (2) 530
- equations for compression of, (2) 530
- load deflection of, (2) 530
- mechanical behavior of, (2) 530
- silicone rubber, (2) 530
- Osmometry, membrane, (1) 15
- Oxetanes, fluorinated, elastomers from, (3) 619
- Oxygen absorption by polymerizable antioxidants, (1) 106
- Ozone, effect of torsional and axial stress on reaction of, (2) 540
- cracking of rubber by, bond rupture, (2) 540
- ESR of, (2) 540
- kinetics of reaction with thiosemicarbazides, (2) 517
- resistance of rubber, tests for, (2) 517
- Particle size, of carbon blacks, (1) 204; (3) 653; (4) 877, 897; (5) 1239
- of light colored fillers, (3) 653
- of protein in natural rubber, (1) 47
- of reclaim rubber, (3) 653
- Particle size, of rubber in blends, (5) 1193
- 1,3-Pentadiene, copolymer with butadiene, (5) 1274
- microstructure in, (5) 1274
- selective polymerization of trans isomer, (5) 1274
- Perfluoroalkylene triazine elastomer, preparation, (3) 619
- properties, (3) 619
- Perfluoro (methyl vinyl ether), copolymers of, (3) 619
- Perfluorothioacetone, elastomers from, (3) 619
- Peroxides, curing agents, for fluoroelastomers, (3) 619
- or poly (ethylene), (4) 1007
- for poly (ethylene co propylene), 1007
- efficiency of crosslinking, (4) 1007
- Peroxide vulcanization, of natural rubber, (5) 1287
- 1,2-Poly (butadiene) as co-agent for, (1) 275
- Phase contrast microscopy, (3) 653
- Piperylene, see 1,3-Pentadiene
- Plasticization rate of natural rubber and poly (isoprene), (1) 47
- Plasticizers for fluoroelastomers, (3) 619
- Poisson's ratio, influence on compression modulus, (1) 286
- Pollution, by tire rubber dust, (1) 232
- Poly (acrylate)s, effect of antioxidants, (5) 1328
- high temperature aging, (5) 1328
- stress relaxation of, (5) 1328
- Poly (acrylate ester co isobutylene), alternating, (4) 1068
- amine cure, (4) 1068
- decomposition temperature, (4) 1068
- flammability, (4) 1114
- oil resistance, (4) 1068
- random, (4) 1068
- solubility parameter, (4) 1068
- sulfur curable, (4) 1068
- tensile strength, (4) 1068
- water resistance, (4) 1068
- Poly (acrylonitrile), (4) 1087
- glass transition temperature, (4) 1087
- solubility parameter, (4) 1087
- Poly (acrylonitrile co butadiene co styrene) measure of ungrafted rubber in, (5) 1327
- Poly (acrylonitrile co styrene), alternating copolymer, (4) 1068
- glass transition temperature, (4) 1068
- properties, 4 1068
- random copolymer, properties, (4) 1068

- Poly (acrylonitrile co vinyl chloride), flammability, (4) 1114
- Poly (butadiene), cis-1,4, (3) 593; (4) 1044, 1055, 1087
- Poly (butadiene), 1,2, (1) 275; (4) 1044 as coagent for peroxide cure, (1) 275
- Poly (butadiene), analysis by gas chromatography, (5) 1326
- blends, with Chlorobutyl rubber, (1) 251
- with natural rubber, (3) 653
- with poly (butadiene co styrene), (3) 653
- with poly (isoprene), (2) 571
- carbon-13 NMR of, (2) 350
- of various microstructures, (2) 350
- carboxyl terminated, (1) 139, 161
- vulcanization of, (1) 139
- Catalysts, (4) 1055
- effect of counter-ion on microstructure, (4) 1055
- catalyzed by n-butyl lithium, (5) 1156
- chain extendable, (1) 161
- cis-trans isomerization of, (5) 1156
- cis-trans linkages in, (5) 1156
- cis-trans ratio in, (5) 1156
- cis-trans triads in, (5) 1156
- compatibility, (5) 5 1210
- convulcanization with Chlorobutyl rubber, (1) 251
- crystallization of, (1) 178
- deformation index, (5) 1166
- distribution of 1,2-units in, (5) 1156
- dynamic properties of, (2) 561; (5) 1330
- elastic modulus and double strain amplitude, (1) 178
- electron microscopy, (1) 178
- effect of carbon black content on crystallization, (1) 178
- effect of mixing method on, (1) 178
- effect of various rubbers on crystallization of, (1) 178
- effect of vinyl content on NMR spectra of, (5) 1156
- energetic contribution to elastic force, cis, (3) 593
- trans, (3) 593
- failure characteristics, (5) 1166
- flammability, (4) 1114
- flow of, (5) 1188
- glass transition temperature, (4) 1087; (5) 1166, 1210
- variation with vinyl content, (5) 1166
- of vulcanized, (5) 1166
- hydrogenated, (2) 470
- hydroxyl terminated, (1) 161
- interfacial bonding of, (1) 251
- effect of crosslink type, (1) 251
- liquid, (1) 139
- dispersion of fillers in, (1) 148
- hydroxyl terminated, (2) 590
- reactively terminated, (1) 148
- low molecular weight, (4) 1055
- as coagent for peroxide cure, (1) 275
- maximum relaxation time, (5) 1166
- mechanical breakdown of, (2) 570
- metalation of, (4) 1044
- with n-butyl lithium, (4) 1044
- microstructure of, (2) 350
- milling variation with deformability, (5) 1166
- mixing character of, (5) 1166
- molecular weight and catalyst compositions, (4) 1055
- molecular weight distribution, (1) 115; (2) 449; (5) 1166
- molecular weight and microstructure, (4) 1055
- Mooney recoil, (5) 1166
- Mooney viscosity, (5) 1166
- 300 Mhz NMR spectra of, (5) 1156
- processability, (5) 1166
- pyrolysis of airborne dusts, of, (1) 232
- rheology of, (5) 1166, 1188, 1193
- solubility parameter, (4) 1087
- stress-optical coefficient, (3) 653
- temperature coefficient of unperturbed dimensions (cis), (3) 593
- trans, (3) 593
- wear of, (4) 787
- wetting index for fillers, (5) 1166
- yield and catalyst compositions, (4) 1055
- Poly (butadiene co acrylonitrile), activation energy of glass transition, (5) 1264
- aging, (4) 927
- of various vulcanizates, (2) 483
- alternation in, (5) 1264
- antioxidants for, (2) 483
- blends with natural rubber and poly (butadiene co styrene), compatibility, (3) 653
- carbon tetrachloride soluble portion, (4) 1087
- carboxylated, (1) 78
- flammability, (4) 1114
- chain branching, (2) 483
- chain scission, (2) 483
- compatibility, (5) 1188, 1210
- complex modulus, (4) 1087
- compression set of, (1) 305
- copolymerization parameters, (4) 1087
- copolymerization with polymerizable antioxidants, (1) 106
- crosslink efficiency of, (2) 483
- crystallinity by x-ray diffraction, (5) 1264
- damping, (4) 1087
- DTA thermogram, (4) 1087
- effect of conversion on composition, (4) 1087
- effect of monomer ratio on composition, (4) 1087
- energetic contribution to elastic force, (3) 593
- filler effect, (4) 927
- flammability, (4) 1114
- flow of, (5) 1188
- gels, (4) 1087
- glass transition, (5) 1210
- heat resistant, (2) 483
- mechanical properties of, (5) 1264
- monomer reactivity ratio, (5) 1264

- multiple glass transition, (4) 1087
- network structure as function of cure time, (2) 483
- oil resistance, (4) 1068
- peroxide cured, (2) 483
- peroxide cure with 1,2-poly (butadiene) as co-agent, (1) 275
- with polymerizable antioxidant, (1) 106
- powdered, (2) 589
- physical properties of, (1) 78
- rheology of, (5) 1188
- scorch control of, (1) 78
- stress birefringence, (5) 1264
- stress-optical coefficient, (3) 653
- temperature coefficient of unperturbed dimensions, (3) 593
- viscoelastic behavior of, (2) 417
- Poly (butadiene co 1,3-pentadiene), cure rate of, (5) 1274
- glass transition temperature, (5) 1274
- melting temperature, (5) 1274
- microstructure, (5) 1274
- oil extension of vulcanizates, (5) 1274
- physical properties of vulcanizates, (5) 1274
- processing of, (5) 1274
- stress crystallization, (5) 1274
- synthesis of, (5) 1274
- tack of, (5) 1274
- tread stocks, (5) 1274
- Poly (butadiene co styrene), Alfin, (2) 587
- gel formation in, (5) 1332
- analyses of, (5) 1326
- blends with other elastomers, (3) 653
- copolymerizable antioxidants for, (1) 96
- copolymerization kinetics, (5) 1322
- copolymerization with copolymerizable antioxidants, (1) 106
- covulcanization with Chlorobutyl rubber, (1) 251
- creep compliance of vulcanizate, (4) 1077
- isochronal plots, (4) 1077
- master curve, (4) 1077
- WLF plots, (4) 1077
- with cycloalkylthioamine acceleration, (1) 67
- deformation diagram, (5) 1166
- die swell of, (5) 1166
- and mixing time, (5) 1166
- distribution of monomer units as function of molecular weight, (2) 449
- dynamic mechanical properties of, (5) 1330
- effect of carbon black on die swell, (5) 1218
- effect of crystallinity of poly (butadiene), (1) 178
- elastic modulus of vulcanizates, (4) 877
- energetic contribution to elastic force, (3) 593
- flammability, (4) 1114
- glass transition temperature, variation with composition, (5) 1166
- heterogeneity of crosslinks, (5) 1285
- interfacial bonding of, (1) 251
- effect of crosslink type, (1) 251
- maximum relaxation time, (5) 1166
- measurement of oil in, (2) 449
- mechanical breakdown of, (2) 570
- milling variation with deformation, (5) 1166
- mixing of, (5) 1166
- molecular weight distribution, (2) 449
- oil resistance, (4) 1068
- ozone cracking of, (2) 540
- with polymerizable antioxidants, (1) 106
- radial block copolymers, (2) 588
- refractive index dispersion, (3) 653
- rheology of, (5) 1166
- starch masterbatches, (2) 589
- stress-optical coefficient, (3) 653
- temperature coefficient of unperturbed dimensions, (3) 593
- theory of ultimate elongation, (1) 242
- weight average molecular weight, (5) 1166
- wetting index for fillers, (5) 1166
- x-ray spectra of, (5) 1285
- Poly (butadiene co vinylpyridine), (5) 1285
- vulcanization by 1,10-dibromodecane, (5) 1285
- Poly (butene-1), energetic contribution to elastic force, (3) 593
- temperature coefficient of unperturbed dimensions, (3) 593
- Poly (butene co propylene) infrared absorbance data, (1) 30
- Poly (n-butyl acrylate), energetic contribution to elastic force, (3) 593
- temperature coefficient of unperturbed dimensions, (3) 593
- Poly (n-butyl acrylate co n-butyl methacrylate), energetic contribution to elastic force, (3) 593
- temperature coefficient of unperturbed dimensions, (3) 593
- Poly (isobutyl acrylate), energetic contribution to elastic force, (3) 593
- temperature coefficient of unperturbed dimensions, (3) 593
- Poly (sec-butyl acrylate), energetic contribution to elastic force, (3) 593
- temperature coefficient of unperturbed dimensions, (3) 593
- Poly (t-butyl acrylate), energetic contribution to elastic force, (3) 593
- temperature coefficient of unperturbed dimensions, (3) 593
- Poly (isobutyl methacrylate), energetic contribution to elastic force, (3) 593
- temperature coefficient of unperturbed dimensions, (3) 593
- trans-1,4-Poly (chlorobutadiene), blends with natural rubber and poly (butadiene co styrene), (3) 653
- energetic contribution to elastic force, (3) 593
- filler effect, (4) 927
- refractive index dispersion, (3) 653
- stress-optical coefficient, (3) 653
- temperature coefficient of unperturbed dimensions, (3) 593

- Poly (chlorobutadiene co acrylonitrile), flammability, (4) 1114
- Poly (chlorotrifluoroethylene co vinylidene fluoride), preparation, (3) 619
- Poly (dimethylsiloxane), energetic contribution to elastic force, (3) 593
- equation-of-state parameters for, (2) 331
- high molecular weight, (2) 831
- O-rings, (2) 530
- load-contact function, (2) 530
- load-deflection curve, (2) 530
- plasticizer for fluorosilicone rubber, (3) 619
- solutions, (2) 338
- temperature coefficient of unperturbed dimensions, (3) 593
- thermodynamics of, (2) 338
- Poly (ethyl acrylate), energetic contribution to elastic force, (3) 593
- temperature coefficient of unperturbed dimensions, (3) 593
- Poly (ethylene), adhesion, (2) 549
- Arrhenius plots for crosslinking, (4) 1007
- chlorinated, flammability, (4) 1114
- chlorosulfonated, flammability, (4) 1114
- contact angles of, (2) 549
- crystallinity in, (1) 7
- variation with temperature, (1) 7
- cure rate with dicumyl peroxide, (4) 1007
- energetic contribution to elastic force, (3) 593
- equation-of-state parameters for, (2) 331
- gas chromatography on stationary phase of, (1) 7
- graft polymer, with poly (styrene), (4) 1044
- with poly (vinylcyclohexane), (4) 1044
- with poly (ethylene co-1-butene), (4) 1044
- processing aid in fluoroclastomers, (3) 619
- rates of crystallization in, (1) 14
- sequence minimum length for crystallinity in copolymers with α -olefins, (1) 30
- temperature coefficient of unperturbed dimensions, (3) 593
- Poly (ethylene co-1-butene), infrared absorbance data, (1) 30
- Poly (ethylene co propylene), analysis by gas chromatography, (5) 1326
- blends with natural rubber and poly (butadiene co styrene), (3) 653
- carbon black in, (3) 653
- compatibility, (5) 1210
- control of structure and properties, (5) 1322
- distribution of carbon black in, (3) 653
- dynamic properties of, (5) 1330
- energetic contribution to elastic force, (3) 593
- glass transition temperature, (5) 1166, 1210
- variation with ethylene content, (5) 1166
- graft polymer with poly (stryene), (4) 1044
- infrared absorbance data, (1) 30
- maximum relaxation time, (5) 1166
- temperature coefficient for unperturbed dimensions, (3) 593
- vulcanization by peroxides, (1) 275; (4) 1007
- weight average molecular weight, (5) 1166
- wetting index for fillers, (5) 1166
- Poly (ethylene co propylene co butene), crosslinking by ionizing radiation, (1) 30
- crystallinity of, (1) 30
- mechanical properties, (1) 30
- polymerization of, (1) 30
- Poly (ethylene co propylene co diene), ethylenenorbornene in, (4) 1019
- determination of, (4) 1019
- flammability, (4) 114
- oil resistance, (4) 1068
- peroxide cure of, (1) 275; (4) 1007
- poly (styrene) graft on, (4) 1044
- properties of filled compounds after aging, (4) 1007
- refractive indices of ^{14}C -ethylenenorbornene containing, (4) 1019
- vulcanizate properties after aging, (4) 1007
- Poly (epichlorohydrin co ethylene oxide), compounding, (2) 557
- Polyester tire cord, adhesion to rubber, (4) 981
- effect of accelerators, (4) 981
- effect of bonding agent, (4) 981
- effect of sulfur concentration, (4) 981
- rubber compounding for, (2) 442
- Poly (1-hydropentafluoropropylene co vinylidene fluoride), preparation, (3) 619
- Poly (2-hydroxypropyl acrylate), energetic contribution to elastic forces, (3) 593
- temperature coefficient of unperturbed dimensions, (3) 593
- Poly (isobutylene co isoprene), see also Butyl rubber
- brominated, flammability, (4) 114
- chlorinated, flammability, (4) 114
- Poly (isobutylene), blends with natural rubber and poly (butadiene co styrene), (3) 653
- energetic contribution to elastic force, (3) 593
- temperature coefficient of unperturbed dimensions, (3) 593
- Poly (isoprene), abstracts of International Symposium on, (2) 555
- aggregate structure in gel of, (5) 1256
- number of molecules in, (5) 1256
- analysis by gas chromatography, (5) 1326
- bonding of vulcanizates of, (2) 580
- breakdown of, (1) 47; (5) 1234
- carbon-13 NMR of, (2) 359; (5) 1126
- of poly (isoprene-3-d.), (2) 359
- of *trans* poly (isoprene), (2) 359
- chemical modification of to improve green strength, (2) 578
- cohesion of, (5) 1234
- comparison with natural rubber, (1) 47; (2) 555, 556, 557, 578, 579
- compatibility, (5) 1210

- crosslink density variation with curvative dispersion, (2) 511
 crystallization, (2) 559
 kinetics of, (1) 22
 in dipped goods, (2) 580
 dispersions of, (2) 566, 580
 dynamic properties, (2) 561; (5) 1330
 economic prospects of, (2) 583
 effect of carbon black on green strength, (5) 1234
 effect of catalyst residues in crystallization of, (2) 559
 effect of crosslinks on rate of crystallization, (5) 1331
 effect of curvative dispersion on properties, (2) 511
 effect of gel on green strength, (5) 1234
 effect of polar groups on green strength, (5) 1234
 energetic contribution to elastic force, (3) 593
 films of, (2) 566
 flammability, (4) 1114
 flow of, (5) 1188
 in foam rubber, (2) 580
 gel content of, (5) 1256
 glass transition temperature, (5) 1210
 graft with poly (styrene), (4) 1044, 1087
 green strength of, (5) 1234
 improvement with nitrosoanilines, (2) 574
 improvement with N, 4-dinitroso-N-methylaniline, (2) 571
 of sol fraction, (5) 1234
 high green strength compound, (2) 557
 high purity, (2) 557
 high temperature vulcanization, (2) 566
 hydroformylation of, (1) 47
 infrared spectra of, (1) 47
 injection molding of, (2) 578
 intrinsic viscosity-molecular weight function, (5) 1256
 mechanical breakdown of, (2) 570
 metalation of, (4) 1044
 with n-butyl lithium, (4) 1044
 microstructure, (2) 359, 556
 modified in tire compounds, (2) 573
 nuclear magnetic resonance, (2) 359; (5) 1126
 in oil-extended carbon-black masterbatches, (2) 574
 plastication rate of, (1) 47
 polymerization catalysts, (2) 555
 properties, dependence on microstructure, (2) 581
 pyrolysis of airborne dusts, (1) 232
 radiothermoluminescence, (5) 1210
 trans, rate of crystallization, (5) 1331
 replacement of natural rubber in truck tires by, (2) 577
 rigid-lattice hydrogen atoms in, (1) 22
 in rubber products, (2) 563
 in rubber thread, (2) 580
 Soviet development in production of, (2) 555
 stabilization of, (2) 569
 Stockmayer-Fixman equations for, (5) 1256
 structure of, (2) 555
 sulfur crosslinking of, (5) 1331
 stress-optical coefficient, (3) 653
 swelling index of gel, (5) 1256
 temperature coefficient of unperturbed dimensions, (3) 593
 of trans, (3) 593
 tensile properties, (2) 558
 variation with curvative dispersion, (2) 511
 in tires, (2) 577, 578
 vulcanization of films of, (2) 566
 Poly (isoprene co acrylonitrile), glass transition temperature, (4) 1087
 Poly (isopropyl acrylate), energetic contribution to elastic force, (3) 593
 temperature coefficient of unperturbed dimensions, (3) 593
 Polymerizable antioxidants, in emulsion rubbers, (1) 106
 preparation and activity of, (1) 96
 Poly (methyl methacrylate), gas chromatographic studies as stationary phase, (1) 1
 glass transition temperature of, (1) 1
 Poly (methylvinylsiloxane), flammability, (4) 114
 Poly (methyl, vinylphenylsiloxane), flammability, (4) 1114
 Polyoxyethylene, energetic contribution to elastic force, (3) 593
 equation-of-state parameters for, (2) 331
 temperature coefficient of unperturbed dimensions, (3) 593
 Polypentenamer, electron microscopy, (5) 1193
 microstructure and polymerization, (5) 1239, 1324
 mixing of, (5) 1193
 molecular weight distribution, (2) 449
 Poly (n-pentene-1), energetic contribution to elastic force, (3) 593
 temperature coefficient of unperturbed dimensions, (3) 593
 Poly [perfluoro (methyl vinyl ether) co tetrafluoroethylene], preparation, (3) 619
 properties, (3) 619
 solvent resistance, (3) 619
 vulcanization, (3) 619
 Poly (perfluoronitrosomethane co tetrafluoroethylene), preparation, (3) 619
 properties, (3) 619
 vulcanization, (3) 619
 Poly (perfluoropropylene co tetrafluoroethylene co vinylidene fluoride), curing agents for, (3) 619
 as plasticizer for fluoroelastomers, (3) 619
 preparation, (3) 619
 Poly (perfluoropropylene co vinylidene fluoride), applications, (3) 619
 carboxyl terminated, (3) 619
 curing agents for, (3) 619

- energetic contribution to elastic force, (3) 593
- preparation, (3) 619
- of polymeric dicarboxylic acids from, (3) 619
- processing, (3) 619
- properties, (3) 619
- review of, (3) 619
- temperature coefficient of unperturbed dimensions, (3) 593
- vulcanizate properties, (3) 619
- Poly (propylene), crystallinity in, (1) 7
- gas chromatography, as stationary phase, (1) 7
- Poly (propylene oxide), flammability, (4) 1114
- Poly (propylene sulfide), energetic contribution to elastic force, (3) 593
- temperature coefficient of unperturbed dimensions, (3) 593
- Poly (styrene), equation-of-state parameters for, (2) 331
- energetic contribution to elastic force, (3) 593
- gas chromatographic studies, as stationary phase, (1) 1
- glass transition temperature of, (1) 1
- molecular weight distribution, (1) 115; (2) 449
- molecular weight by electron microscopy, (3) 653
- temperature coefficient of unperturbed dimensions, (3) 593
- Poly (tetramethylene oxide), energetic contribution to elastic force, (3) 593
- temperature coefficient of unperturbed dimensions, (3) 593
- Poly (3,3,3-trifluoropropylene), energetic contribution to elastic force, (3) 593
- temperature coefficient of unperturbed dimensions, (3) 593
- Poly (trifluoropropylene methylsiloxane), preparation, (3) 619
- properties, (3) 619
- solvent resistance, (3) 619
- Polyurethanes, for automobile bumpers, (4) 843
- energy absorbers, (4) 843
- foams, effect of density on stress, (4) 843
- effect of skin on dynamic performance, (4) 843
- effect of temperature on deflection, (4) 843
- load-deflection curve of, (4) 843
- static stress, (4) 843
- velocity response of, (4) 843
- polyester, flammability, (4) 1114
- polyether, flammability, (4) 1114
- Poly (vinyl chloride), energetic contribution to elastic force, (3) 593
- gas chromatographic studies, as stationary phase, (1) 1
- molecular weight distribution, (1) 115
- temperature coefficient of unperturbed dimensions, (3) 593
- Poly (vinylcyclohexane), graft on polyethylene, (4) 1044
- Powdered rubber, economic analysis of use of, (5) 1334
- poly (butadiene co acrylonitrile), (2) 589
- starch xanthate encased, (2) 590
- technology, (2) 589, 591
- Prevulcanization inhibitors, see also Scorch inhibitors and Retarders
- accelerators, (2) 504
- effect of zinc complex, (2) 504
- mechanism of, (2) 504
- Processability, (5) 1188, 1193, 1218
- of fluoroelastomers, (3) 619
- Protein, amino acid content of, in natural rubber, (1) 47
- analysis of amino acids by gas chromatography, (1) 47
- effects on properties of natural rubber, (1) 47
- filler effect in natural rubber, (1) 47
- Pyrolysis chromatograms, of airborne dusts, (1) 232
- in polymer analyses, (5)
- Radiation curing, of fluoroelastomers, (3) 619
- Radicals, generated by oxidation of antioxidants, (5) 1134
- mechanism of degeneration, (5) 1134
- Radioactivity, analysis by, (4) 1019
- determination of ethylenenorbornene by, (4) 1019
- of iodine, (4) 787
- Radio-frequency-activated gas to improve adhesion, (2) 549
- Radiothermoluminescence, (5) 1188
- method of measuring glass transition temperature, (5) 1188
- Raman spectra (laser beam), dimethyl dimethylthiocarbamyl sulfenamide, (4) 938
- of sulfur, (4) 938
- of tetramethylthiourea, (4) 938
- tetramethylthiuram mono-, di, and tetrasulfides, (4) 938
- zinc dimethyldithiocarbamate, (4) 938
- Rayon tire cord, adhesion to rubber, (4) 981
- bonding agent for, (4) 981
- effect of accelerators, (4) 981
- effect of sulfur dosage, (4) 981
- Reactivity ratios, determination of, (1) 30
- for α -olefin terpolymers, (1) 30
- for butadiene-acrylonitrile, (4) 1087
- isoprene-acrylonitrile, (4) 1987
- Reclaimed rubber in vulcanizates, detection, (3) 653
- microscopy, (3) 653
- Reference chain dimensions, (1) 127
- Refractive index, carbon-14 poly (ethylene co propylene co ethylenenorbornene), (4) 1019
- dispersion of rubbers, (3) 653
- by interference microscopy, (3) 653
- of rubbers, (3) 653

- Relaxation, of compression, (5) 1316
diffusion controlled, (5) 1316
- Relaxation time, effect of carbon black, (5) 1218
maximum, (5) 1166
- Rheology, of blends, (5) 1193
effect of strain rate, (5) 1188
of liquid elastomers, (1) 161
- Retarders, (4) 981, 999
of cure, reaction scheme, (4) 999
effect on rubber-cord adhesion, (4) 981
- Ring specimens, in tensile testing, (2) 586
- Road surface, effect on tire surface temperature, of temperature of, (4) 821
effect of texture on tire wear, (4) 801, 821
effect of weather on, (4) 801, 821
- Rubber Division, best paper awards, (3) G44; (5) G89
bylaws, (1) G27
future meetings, (1) G5; (2) G43; (3) G57; (4) G57; (5) G87
future meeting symposia, (1) G6; (2) G44; (3) G58; (4) G76
Goodyear medalist, (2) G45
address, (2) G48
library and information service, (1) G2; (2) G40; (3) G54; (4) G72; (5) G84
officers and steering committee, (1) G1; (2) G39; (3) G53; (4) G71; (5) G82
program for Fall meeting, (4) G77
program for Spring meeting, (1) G8
steering committee, (1) G1; (2) G39; (3) G53; (4) G71; (5) G83
- Rubber elasticity, and compression modulus, (5) 1287
molecular interpretation of, (3) 593
statistical theory of, (3) 593; (5) 1287
theory compared to experiment, (5) 1287
thermodynamics of, (3) 593
- Scorch control, of carboxylic elastomers, (1) 78
- Scorch inhibitors, see also Prevulcanization inhibitors and Retarders
mechanism of, (1) 47
of sulfur-free thiuram vulcanization, (2) 504
various compounds for, (1) 47, 78
- Scorch of fluoroelastomers, (3) 619
- Seals, rubber, (5) 1333
- Shear modulus, effect of pressure, (5) 1287
effect of volume, (5) 1287
entropy component of, (5) 1287
internal energy component of, (5) 1287
at low strain, (5) 1287
of natural rubber as function of temperature, (5) 1287
- Shear stress, (5) 1166
melt viscosity, (5) 1193
and time, (5) 1193
- Shell, flexure, model for belted tire, (1) 294
theory, (1) 294
- Silica, filler for fluoroelastomers, (3) 619
microscopy of, in vulcanizates, (3) 653
reinforcement of liquid elastomers, (1) 161
- Solubility parameter and poly (butadiene) crystallinity, (1) 178
- Solutions, thermodynamic properties of poly (dimethylsiloxane), (2) 338
- Solvent-resistance, of fluoroelastomers, (3) 619
- Solvents for rubber, equation-of-state for, (2) 338
- Starch masterbatches, with poly (butadiene co styrene), (2) 589
- Starch xanthide, for encasing powdered rubber, (2) 590
filled elastomers, vulcanizates, (2) 589
- Stark rubber, crystallinity in, (1) 22
- Strain amplitude, (4) 877, 897
effect on elastic modulus, (4) 877, 897
of natural rubber compounds, (4) 897
- Strain energy density, of tire cord, (1) 294
- Strain energy function, linear combination of strain invariants, (2) 398
- Strain hardening, (5) 1166
- Steel tire cord, adhesion to rubber, (4) 981
effect of accelerators, (4) 981
effect of bonding agent, (4) 981
effect of sulfur concentration, (4) 981
- Stress, ozone attack and, (2) 540
axial, (2) 540
torsional, (2) 540
variation, with extension ratio, (5) 4
with temperature, (3) 593
- Stress analyses, of belted tires, (1) 294
- Stress-optical coefficient, determination of, (3) 653
of natural rubber, (3) 653
of poly (butadiene co acrylonitrile), (5) 1264
- Stress relaxation, chemical, (2) 388, 477
continuous, (2) 483
intermittent, (2) 388, 483
at large deformation, (2) 388
of natural rubber vulcanizates at high temperature, (2) 388
of poly (butadiene co styrene), (2) 417, 488
- Stress-strain, high speed, (2) 417
isothermal, (2) 398
of poly (butadiene co acrylonitrile), (2) 417
- Styrene-butadiene rubber, see Poly (butadiene co styrene)
- Sulfenamides, adhesion in presence of, (4) 981
scorch inhibitors of sulfur-free thiuram vulcanization, (2) 504
- Sulfur-free thiuram vulcanization, (2) 504
- Sulfur, kinetics of consumption in vulcanization, (2) 511
Raman spectrum of, (4) 938
- Surface area of carbon blacks, comparison of measuring methods, (1) 192
- Tack, of poly (butadiene co 1,3-pentadiene), (5) 1274
of poly (isoprene), (2) 571
- Tan δ , see also hysteresis
by nonresonant measurement, (4) 897
by rebound, (4) 897

- Temperature-frequency transposition, (4) 877
- Tensile strength, of poly (isoprene)s, (2) 558
- effect of test temperature, (2) 560
- ring specimens for measurement, (2) 586
- rupture theory, (1) 242
- temperature dependence, (1) 242
- ultimate, of vulcanizates, (1) 242
- dependence on elongation rate, (1) 242
- Tetrafluorocyclobutanedione, copolymer with thiocarbonyl fluoride, (3) 619
- Tetrafluoroethylene copolymers, preparation, (3) 619
- properties, (3) 619
- review, (3) 619
- vulcanization, (3) 619
- Tetramethylthiourea, Raman spectrum, (4) 938
- Tetramethylthiuram disulfide, electron spin resonance spectrum, (4) 957
- Raman spectrum, (4) 938
- thermal degradation of, (4) 957
- Tetramethylthiuram monosulfide, electron spin resonance spectrum, (4) 957
- Raman spectrum, (4) 938
- Tetramethylthiuram tetrasulfide, infrared spectrum, (4) 938
- Raman spectrum, (4) 938
- Textile fibers, for reinforcing liquid elastomers, (1) 148
- Thermal expansion of poly (dimethylsiloxane), (2) 331
- Thermal pressure coefficient, of poly (dimethylsiloxane), (2) 331
- Thermodynamics, of poly (dimethylsiloxane) mixtures, (2) 338
- of elastomers, (2) 331
- Thermodynamics, of rubberlike elasticity, (3) (593)
- Thermoxidative aging, of poly (butadiene co acrylonitrile), (2) 483
- Thermoplastic elastomers, by styrene grafts, (4) 1044
- Thiocarbonyl fluoride, elastomers from, (3) 619
- synthesis, (3) 619
- Thiosemicarbazides, as age resistors, (2) 517
- derivatives as non-staining antioxidants, (2) 517
- effect on properties of natural rubber, (2) 547
- Thiourea, derivatives as products of zinc dialkylthiocarbamate decomposition, (2) 524
- Tires, belted, stress analysis of, (2) 425
- Carcass, compounds free of amine accelerators, (2) 442
- compound for polyester tire cord, (2) 442
- equation for energy loss, (2) 425
- equation for rolling resistance, (2) 425
- energy losses due to rolling tire, (2) 425
- compounds, poly (isoprene), (2) 579
- energy losses, mechanism of, (2) 425
- energy losses on rolling, (2) 425, 573
- distribution of, (2) 425
- force levels, (4) 821
- lateral and longitudinal, (4) 821
- hysteretic losses on rolling, (2) 425
- poly (isoprene) in, (2) 573
- sectional and whole in testing, (4) 801
- tread, equation for bending losses, (2) 425
- equation for compressive losses, (2) 425
- Tire cord, equation for energy loss of, (2) 425
- energy losses during tire operation, (2) 425
- energy losses due to, in rolling tires, (2) 425
- polyester, adhesion to rubber, (2) 442
- strain energy density, (1) 294
- Tire dust, determination of, in atmosphere, (1) 232
- Tire wear, bias vs radial tires, (4) 821
- calibration of, (4) 787
- comparison of elastomers, (2) 586
- controlled conditions for, (4) 801
- crown to shoulder ratio, (4) 801
- depth gage for, (4) 787
- driving conditions, (2) 586
- effect of antioxidant in natural rubber, (4) 821
- effect of cornering, (4) 801, 821
- pavement, (4) 801
- slip angle, (4) 801
- tire orientation, (4) 801
- effect of cure system and natural rubber and poly (butadiene co styrene), (4) 821
- effect of load on, (4) 801
- effect of operational mode, (4) 821
- effects of road surfaces, (2) 586; (4) 821
- effect of road weathering, (4) 801
- effect of slip angle, (4) 801, 821
- effect of tire surface temperature, (4) 821
- effect of wet road surface, (4) 821
- equation for, (4) 801
- exponent in rate equation for, (4) 821
- effect of tint and DBP number of carbon black, (4) 821
- effect of severity index gradient, (4) 821
- factors in mechanism of, (4) 801
- fleet tests vs trailer tests, (4) 821
- as function of carbon black particle shape, (1) 204
- measurement at low mileage, (4) 787
- measurement by radiiodine, (4) 787
- severity index gradient, (4) 821
- effect of iodine number, DBP number, and tint of carbon black to, (4) 821
- severity of wear test, (4) 821
- surface temperatures of tire and, (4) 801, 821
- test system for, (4) 801
- trailer for measuring, (4) 801
- mechanical controls for, (4) 801
- wear curves for test trailer, (4) 801
- Titanium dioxide, in vulcanizates, microscopy, (3) 653
- Torsional pendulum, (2) 561
- Torsional loading, of poly (butadiene co styrene), (2) 540
- Trailer, for tire wear measurement, (4) 801
- cornering wear, (4) 801
- wear curves for, (4) 801

- Truck tires, poly (isoprene) in, (2) 563, 577
 1,1,4-Tributylthiosemicarbazide, as non-staining antiozonant, (2) 517
 Tributylthiourea, (2) 517
 Tyndall effect in rubbers, (3) 653
- Unperturbed dimensions of polymer chain, measure of, (3) 593
 temperature coefficient of, (3) 593
 theory of, (3) 593
 thermoelastic measurements, (3) 593
 from viscosity measurements, (3) 593
- Urea-formaldehyde pigments, for liquid elastomers, (1) 161
- Vinyldioxolanes, fluorinated elastomers from, (3) 619
 Vinyl ethers, fluorinated elastomers from, (3) 619
 Vinylidene fluoride copolymers, comonomers, (3) 619
 curing agents for, (3) 619
 preparation, (3) 619
 processing, (3) 619
 properties of, (3) 619
 review, (3) 619
 vulcanizates, (3) 619
- Viscoelastic parameters, tire carcass, (2) 425
 tire-cord system, (2) 425
 tire sidewall, (2) 425
 tire tread bending, (2) 425
 tire tread compression, (2) 425
- Viscoelasticity, at large deformations, (2) 417
 molecular theory of, of polymer networks, (1) 127
 in O-rings, (2) 530
 of poly (butadiene co acrylonitrile), (2) 417
 of raw compounds, effect of curative dispersion, (2) 511
 at small deformations, (2) 417
 of tire components, (2) 425
- Viscosity, shear, zero, (5) 1166
 melt, (5) 1193
 variation of time and shear, (5) 1193
- Viton, A, see poly (perfluoropropylene co vinylidene fluoride)
- Vulcanizates, elastic modulus of, (4) 877
 electron micrograph of section, (3) 65; (4) 877
 heat stability of, (4) 927
 heterogeneity of crosslinks in, (5) 1285
 identification of accelerators in, (4) 1035
 of poly (butadiene co 1,3-pentadiene), (5) 1274
 of poly (ethylene co propylene co diene), (4) 1007
- Vulcanization, see also Crosslinking
 Butyl rubber, (2) 584
 carboxyl terminated poly (butadiene), (1) 139
 Chlorobutyl rubber, (1) 251
 effect of curative dispersion on, (2) 511
 of fluoroelastomers, (3) 619
 high temperature, (2) 566
 of liquid elastomers, (1) 139, 161
 mechanism of, (4) 957
 of natural rubber, (1) 67, 305; (2) 477, 504, 556, 557, 558, 561, 566, 578, 584; (3) 653; (4) 874, 981, 999; (5) 1299
 of poly (butadiene), (1) 251; (2) 561, 588
 1,2-polymer, (1) 275
 of poly (butadiene co acrylonitrile), (1) 275, 305; (2) 483, 584
 of poly (butadiene co 1,3-pentadiene), (5) 1274
 of poly (butadiene co styrene), (1) 251; (2) 442, 592
 containing chemically attached antioxidants, (1) 106
 of poly (chlorobutadiene), (2) 584
 of poly (ethylene co propylene), (2) 1007
 of poly (isoprene), (2) 442, 556, 557, 558, 566, 578
 scorch delay mechanism, (1) 47
 by various accelerators, (1) 47
- Vulcanization by-products, observed microscopically, (3) 653
 rate, effect of accelerators on, (2) 504
- Wetting index, for fillers, (5) 1166
 Wetting time, of elastomers for fillers, (5) 1166
 WLF superposition, (1) 127
- Young's modulus, (1) 294
- Zinc chloride, divinylpyridino, (5) 1285
 vulcanization of poly (butadiene co styrene) by, (5) 1285
- Zinc complexes, effect on prevulcanization inhibition, (2) 504
 mechanism of decomposition, (2) 524
 in mechanism of vulcanization, (4) 938
 thermal decomposition of, (2) 524; (4) 938
- Zinc dimethyldithiocarbamate, decomposition, (2) 524
 Raman spectrum of, (4) 938
- Zinc oxide, coated, in carboxylic elastomers, (1) 78
 encapsulating for scorch control, (1) 78
 in fluoroelastomer, vulcanization, (3) 619
 in vulcanizates, microscopy, (3) 653
- Zinc phosphate, coating on zinc oxide, (1) 47
 Zinc sulfide, coating on zinc oxide, (1) 78
 as vulcanization by-product, (3) 653
 in vulcanization, microscopy, (3) 653



